

Refrigerator, compressor, E1134CZA, 1/2 hp, E1130CZA, E1121CZA, 3/8HP, commercial, freezer, R134a

written by Lilianne | 6 April 2021

Refrigerator, compressor, E1134CZA, E1130CZA, E1121CZA, 3/8HP,
commercial, freezer, R134a

MBSM.PRO, All Compressor in One File , Pdf and Print

written by Lilianne | 6 April 2021



MBSM.PRO, All Compressor in One File , Pdf and Print

**RÉFRIGÉRATEUR NIKAI,
nrf480fn4, 165W, Compressor,
ATD60L, Wanbao Huaguang
Refrigerator, 1/5Hp, R134A,
120G, 1.25A, 220V/50HZ**

written by Lilianne | 6 April 2021



RÉFRIGÉRATEUR NIKAI, nrf480fn4, 165W, Compressor, ATD60L, Wanbao Huaguang Refrigerator, 1/6Hp, R134A, 120G, 1.25A, 220V/50HZ

Compressor, 1/3HP, FR10S, 103U2930, SECOP, 103U, 2930, Compressor Danfoss, R12, 220-240V, 50Hz

written by Lilianne | 6 April 2021

- DESCRIPTION

DESCRIPTION



FR10S

220-240V-60Hz

LBP LST/HST

220-240V-50Hz

LBP/HBP LST/HST

SECO

Formerly Danfoss Compressors



888K1025

103U

2930

MADE IN SLOVENIA

CE

R404a / R507a				
13	104L2523	Danfoss Compressor SC 10CL	1/3 HP	352 W
14	104L2623	Danfoss Compressor SC 12CL	3/8 HP	445 W
15	104L2853	Danfoss Compressor SC 15CL	1/2 HP	560 W
16	104L2123	Danfoss Compressor SC 18CL	5/8 HP	615 W
17	104L2322	Danfoss Compressor SC 21CL	7/8 HP	702 W

Private Picture Copyright : WWW.MBSM.PRO

R134a				
9	104G8240	Danfoss compressor SC 12G	3/8 HP	298 W
10	104G8520	Danfoss compressor SC 15G	1/2 HP	356 W
11	104G8820	Danfoss compressor SC 18G	5/8 HP	615 W
12	104G8140	Danfoss compressor SC 21G	7/8 HP	702 W

Private Picture Copyright : WWW.MBSM.PRO



Mbsm_dot_pro_private_PDF_103u2930-compressorTélécharger

Mbsm_dot_pro_private_PDF_103u2930Télécharger

Sr	Material	Material Description	Capacity	Cons. Watts -25
R134a				
1	103G6660	Danfoss Compressor FR 6G	1/6 HP	119 W
2	103G6680	Danfoss compressor FR 7.5G	1/5 HP	138 W
3	103G6780	Danfoss compressor FR 8.5G	1/4 HP	164 W
4	103G6880	Danfoss compressor FR 10G	1/3 HP	194 W
R12a				
5	103G2630	Danfoss compressor FR 6S	1/6 HP	119 W
6	103U2730	Danfoss compressor FR 7.5S	1/5 HP	138 W
7	103U2830	Danfoss compressor FR 8.5S	1/4 HP	164 W

8	103U2930	Danfoss compressor FR 10S	1/3 HP	194 W
		R134a		
9	104G8240	Danfoss compressor SC 12G	3/8 HP	298 W
10	104G8520	Danfoss compressor SC 15G	1/2 HP	356 W
11	104G8820	Danfoss compressor SC 18G	5/8 HP	615 W
12	104G8140	Danfoss compressor SC 21G	7/8 HP	702 W
		R404a / R507a		
13	104L2523	Danfoss Compressor SC 10CL	1/3 HP	352 W
14	104L2623	Danfoss Compressor SC 12CL	3/8 HP	445 W
15	104L2853	Danfoss Compressor SC 15CL	1/2 HP	560 W
16	104L2123	Danfoss Compressor SC 18CL	5/8 HP	615 W
17	104L2322	Danfoss Compressor SC 21CL	7/8 HP	702 W

COMPRESSOR, DONPER, NE6213CK, 1/2hp, R404a

written by Lilianne | 6 April 2021

Ne6213Ck Compressor R404A Med Temp 12 Disp 1080W @ -5 1/2Hp
240V 50Hz



Private Picture Copyright : WWW.MBSM.PRO



NE6213CK COMPRESSOR R404A MED TEMP 12 DISP
1080W @ -5 1/2HP 240V 50HZ

Displacement: 12 cm³

Power: 1/2 HP

Oil Charge: 450 +/- 10 mL

Cooling capacity: 1080W @-5 SST

COP: ASHRAE 1.80

Private Picture Copyright: WWW.MBSM.PRO



Mbsm_dot_pro_private_PDF_ne6213ck-compressorTélécharger

Cubigel Compressors, Compressor, GQY80AT, 1/4Hp, LBP, R134a, 8.1cmc, 165 W, REFRIGERATEUR INDESIT

written by Lilianne | 6 April 2021

Compresor GQY80AT, freon R134a, capacitate 8.1
cmc, capacitate frigorifica ASHRAE 222 W, capacitate
frigorifica CECOMAF 165 W, racire statica #GQY80AT

Model: GQY80AT

Freon: R134a

Capacitate: 8.1 cmc

Capacitate frigorifica ASHRAE: 222 W

Capacitate frigorifica CECOMAF: 165 W

35 -30 -25 -10 w COP

• 451.00.3301 GD40AAa / GVY40AA 1/10 S 4.03 34 49 70 0.77 154 C 200 6.7 RSIR P •

451.00.3202 GD40AA 1/10 S 4.03 34 49 70 0.77 154 C 200 6.7 RSIR P •

• 451.00.3302 GL45AA / GVY44AA 1/8 S 4.55 37 56 81 0.81 183 C 265 8.3 RSIR P •

• 451.00.3303 GL60AA / GVY57AA 1/6 S 5.99 50 75 107 0.85 238 C 265 9.1 RSIR P •

• 451.00.3304 GL75AA / GVY66AA 1/5 S 6.65 57 85 121 0.87 267 C 345 9.6 RSIR P •

• 451.00.3305 GL80AA / GVY75AA 1/5 S 7.52 68 101 144 0.89 326 C 345 9.9 RSIR P •

451.00.3104 GL80AAb 1/5 OC 8.10 68 101 144 0.89 326 C-V 345 9.9 CSIR R •

451.00.3005 GL90AA 1/4 S 9.08 82 119 165 0.90 350 C 345 10.2 RSIR P •

• 451.00.3306 GL90AAa / GQY80AT 1/4 S 9.08 82 119 165 0.90 350 C 345 10.2 RSIR P •

451.00.3105 GL90AAb 1/4 OC 9.08 82 119 165 0.90 350 C-V 345 10.2 CSIR R •

• 451.00.3205 GL90AAb 1/4 F 9.08 82 119 165 0.90 350 C-V 345 10.2 CSIR R •

• 451.00.3325 GL90AAa 1/4 OC 9.08 82 119 165 0.90 350 C-V 345 10.2 CSIR R •

451.00.3106 GP12BB 1/3 OC 12.00 83 131 190 0.88 424 C 400 11.5 RSIR R •

• 451.00.3206 GP12FB 1/3 F 12.00 83 131 190 0.88 424 C 400 11.5 RSIR R •

• 451.00.3326 GP12BB 1/3 OC 12.00 83 131 190 0.88 424 C 400 11.5 RSIR R •

451.00.3218 GP14CB 3/8 F 14.17 99 158 228 0.90 509 C 400 11.5 RSIR R •

451.00.3223 GP16FB 3/8 F 16.15 109 182 266 0.89 585 C-V 530
12.0 CSIR R •

451.00.3224 GX18FB 3/7 F 18.40 123 199 291 0.91 660 C-V 500
15.1 CSIR R •

451.00.3225 GX21FB 2/3 F 20.72 151 243 351 0.93 778 C-V 500
15.5 CSIR R •

451.00.3403 GL45TB 1/6 F 4.50 76 134 342 1.62 412 C-V 300 8.4
CSIR R •

- 451.00.3503 GL45PB 1/6 F 4.50 76 134 342 1.62 412 C-V 300
8.4 CSIR R •

451.00.3404 GL60TB 1/5 F 5.67 95 170 437 1.82 527 C-V 300 9.5
CSIR R •

- 451.00.3504 GL60PB 1/5 F 5.67 95 170 437 1.82 527 C-V 300
9.5 CSIR R •

451.00.3406 GL80TB 1/5 F 7.57 111 212 554 1.83 667 C-V 300 9.5
CSIR R •

- 451.00.3505 GL90TB 1/4 F 8.85 142 259 661 1.91 796 C-V 300
10.8 CSIR R •
- 451.00.3506 GP12TB 3/8 F 12.05 169 338 893 1.80 1077 C-V 350
11.2 CSIR R •

451.00.3418 GP14TB 3/8 F 14.00 190 373 999 1.77 1208 C-V 400
11.5 CSIR R •

- 451.00.3513 GP14TB 3/8 F 14.00 190 373 999 1.77 1208 C-V 400
11.5 CSIR R •

451.00.3419 GX18TB 1/2 F 18.40 285 539 1390 1.91 1673 C-V 500
16.0 CSIR R •

451.00.3420 GX21TB 5/8 F 20.72 332 603 1550 1.90 1866 C-V 500
17.0 CSIR R •

451.00.3421 GX23TB 5/8 F 23.20 368 677 1730 1.89 2083 C-V 500
17.0 CSIR R •

- 451.00.3422 GS26TB 3/4 F 25.93 392 771 2071 2.09 1011 C-V
887 22.7 CSIR R •

451.00.3423 GS30TB 7/8 F 29.95 317 785 2452 2.33 3020 C-V 887
22.7 CSR R •

- 451.00.3424 GS34TB 1 F 34.42 476 1068 2852 2.28 3421 C-V 887
22.7 CSR R •



Private Picture Copyright : WWW.MBSM.PRO

BAJA presión		serie LBP										R-134a				
CÓDIGO REMLE	MODELO	Potencia	Enfri.	Cilindr.	Producción Frigorífica en Watios.					Expansión	Aceite cm3	Peso Kg.	Motor	Aranque	220-240V/50Hz	
* Gases sustitutivos del R-12 y R-134a.					CECOMAF (W)											
o Últimas existencias					-35	-30	-25		-10							
					w	COP										
• 451.00.3301	GD40AAa / GYY40AA	1/10	S	4.03	34	49	70	0.77	154	C	200	6.7	RSIR	P	•	
• 451.00.3202	GD40AA	1/10	S	4.03	34	49	70	0.77	154	C	200	6.7	RSIR	P	•	
• 451.00.3302	GL45AA / GYY44AA	1/8	S	4.55	37	56	81	0.81	183	C	265	8.3	RSIR	P	•	
• 451.00.3303	GL60AA / GYY57AA	1/6	S	5.99	50	75	107	0.85	238	C	265	9.1	RSIR	P	•	
• 451.00.3304	GL75AA / GYY66AA	1/5	S	6.65	57	85	121	0.87	267	C	345	9.6	RSIR	P	•	
• 451.00.3305	GL80AA / GYY75AA	1/5	S	7.52	68	101	144	0.89	326	C	345	9.9	RSIR	P	•	
• 451.00.3104	GL80AAb	1/5	OC	8.10	68	101	144	0.89	326	C-V	345	9.9	CSIR	R	•	
• 451.00.3005	GL90AA	1/4	S	9.08	82	119	165	0.90	350	C	345	10.2	RSIR	P	•	
• 451.00.3306	GL90AAa / GQY80AT	1/4	S	9.08	82	119	165	0.90	350	C	345	10.2	RSIR	P	•	
• 451.00.3105	GL90AAb	1/4	OC	9.08	82	119	165	0.90	350	C-V	345	10.2	CSIR	R	•	
• 451.00.3205	GL90AAa	1/4	F	9.08	82	119	165	0.90	350	C-V	345	10.2	CSIR	R	•	
• 451.00.3325	GL90AAa	1/4	OC	9.08	82	119	165	0.90	350	C-V	345	10.2	CSIR	R	•	
• 451.00.3106	GP12BB	1/3	OC	12.00	83	131	190	0.88	424	C	400	11.5	RSIR	R	•	
• 451.00.3206	GP12FB	1/3	F	12.00	83	131	190	0.88	424	C	400	11.5	RSIR	R	•	
• 451.00.3326	GP12BB	1/3	OC	12.00	83	131	190	0.88	424	C	400	11.5	RSIR	R	•	
451.00.3218	GP14CB	3/8	F	14.17	99	158	228	0.90	509	C	400	11.5	RSIR	R	•	
451.00.3223	GP16FB	3/8	F	16.15	109	182	266	0.89	585	C-V	530	12.0	CSIR	R	•	
451.00.3224	GX18FB	3/7	F	18.40	123	199	291	0.91	660	C-V	500	15.1	CSIR	R	•	
451.00.3225	GX21FB	2/3	F	20.72	151	243	351	0.93	778	C-V	500	15.5	CSIR	R	•	

Private Picture Copyright: WWW.MBSM.PRO

-
-
-
-
-
-
-
-

Mbsm_dot_pro_private_PDF_GQY80ATTélécharger

Tecumseh, Compressor, 5/8HP, HMBP – R404A , R448A , R449A, MBP, CAJ9480Z, 230V

written by Lilianne | 6 April 2021

Caractéristiques techniques

- Marque : TECUMSEH UNITÉ HERMÉTIQUE
- Modèle : CAJ9480Z-R

- CYLINDRÉE (CM³) 15,2
- FLUIDER404A , R448A , R449A
- APPLICATIONHMBP
- PLAGÉ D'APPLICATION-25/+15
- PUISSANCE (W)1159
- PUISSANCE FRIGORIFIQUE (TK+40°C)15/3350 5/2355 -10/1294
-25/609
- TENSION (V)240/1/50
- DÉMARRAGECSR
- I.MAX (A)6,7
- Ø ASPIRATION1/2
- Ø REFOULEMENT5/16
- DIMENSIONS (MM)235x178x280

- Gaz: **R-404a**
- Température/Pression: **Haute Pression**
- Puissance: **5/8 HP**
- Voltage: **230 V**
- Type De Courant: **Monophasé**
- Fréquence: **50 Hz**
- Type De Compresseur: **Hermétique**
- Décalage: **15.2 cm³**
- Cons.Énergie -25°C: **496 W**
- Cons.Énergie -10°C: **669 W**
- Cons.Énergie -5°C: **718 W**
- Cons.Énergie 0°C: **762 W**
- Cons.Énergie +5°C: **798 W**
- Cons.Énergie +10°C: **828 W**
- T° De Condensation: **40 °C**
- Capacidad Frigorífica -25°C: **524 Kcal/h**
- Capacidad Frigorífica -20°C: **692 Kcal/h**
- Capacidad Frigorífica -15°C: **887 Kcal/h**

- Capacidad Frigorífica -10°C: **1113 Kcal/h**
- Capacidad Frigorífica -5°C: **1374 Kcal/h**
- Capacidad Frigorífica 0°C: **1677 Kcal/h**
- Capacidad Frigorífica 5°C: **2025 Kcal/h**
- Capacidad Frigorífica 10°C: **2425 Kcal/h**
- Tipo Test: **EN.12900**

Compresseur L'unité Hermetique – Tecumseh CAJ9480Z – R404A, R449A, R407A, R452A

220 – 240V 1~ 50 Hz

Cylindrée = 15.2 CM3

APPLICATIONS = HBP / MHBP

Moteur type: CSR





Private Picture Copyright : WWW.MBSM.PRO

-
-
-
-
-
-
-

Mbsm_dot_pro_private_PDF_caj9480Z_2494-spec Télécharger

Compresseur AJ = Le produit de référence associant silence, fiabilité et efficacité du froid commercial.

Product Code	Model Number	Compressor Horsepower	Compressor Displacement	Cooling	Oil Charge
	CAJ9480Z-FZ	5/8 HP	15.2 cm ³ /rev	Fan	475 ml
	CAJ9510Z-FZ	1 HP	18.3 cm ³ /rev	Fan	475 ml
	CAJ9513Z-FZ	1 1/8 HP	24.2 cm ³ /rev	Fan	475 ml
	CAJ4517Z-FZ	1.25 HP	25.95 cm ³ /rev	Fan	475 ml
	TAJ4517Z-TZ	1.25 HP	25.95 cm ³ /rev	Fan	475 ml

Product Code	Model Number	Compressor Horsepower	Compressor Displacement	Cooling	Oil Charge
	CAJ4519Z-FZ	1.5 HP	34.45 cm ³ /rev	Fan	475 ml
	TAJ4519Z-TZ	1.5 HP	34.45 cm ³ /rev	Fan	475 ml

Compressor, ACC, Cubigel, GL60AN, R134a, 220-240V, HMBP, 1/6HP

written by Lilianne | 6 April 2021

Type: Hermetic piston compressors Producer: ACC Series: HMBP

Model: GL60AN

General data

Refrigerant:	R134a
Discharge element:	C
Cooling:	S
Maximum ambient temperature [°C]:	50

Compressor's data

Cylinder capacity [cm ³]:	6
Displacement [m ³ /h]:	1
Weight [kg]:	9,9
Oil charge [cm ³]:	345
Oil type:	ISO VG 19 ESTER

Engine's data

Engine type:	RSIR
--------------	------

Power [KM]:	1/6
Starting element:	LST
Power supply:	220V 50Hz
Voltage range:	170-264
Locked rotor current [A]:	14,6
Running winding resistance (25°C) [Ω]:	9,33
Starting winding resistance (25°C) [Ω]:	10,81

Electrical data

Relays:	3003
Shielding element:	MRA38085, T0515, AF11BJ
Starting capacitor volume [μ F]:	

Connections

	millimeters	inches
Suction tube:	6,5	
Service tube:	6,5	
Discharge tube:	4,9	



Private Picture Copyright : WWW.MBSM.PRO

Mbsm_dot_pro_private_PDF_GL60ANTélécharger

Compressor, ROHS, 1/3HP, R134A, Tecumseh, CAE4448Y, HBP, 208V/50HZ 230V/60HZ

written by Lilianne | 6 April 2021



Private Picture Copyright: WWW.MBSM.PRO

Basic Info.

Model NO.

CAE4448Y

Refrigerant Type

Ammonia

Refrigerant

R134A

Voltage

208V/50Hz 230V/60Hz

Horsepower

1/3HP

Capacity(W)

519W

Input Power(Kw)

400W

Oil Charge (Cm3)

450

Net Weight(Kg)

12kg

Cop(W/W)

1.64

Trademark

tecumseh

Transport Package

Wooden Box

Specification

208V/50HZ 230V/60HZ

Origin

France

HS Code

8414309010

**1/3HP HBP Original Made in France R134A Tecumseh Compressor
CAE4448Y Refrigerator Compressor For
Refrigerator/Showcase/Cold Room**

Product Description

Model: CAE4448Y

Brand : Tecumseh

Type: hermetic

Refrigerant: R134A

Voltage: 208V/50HZ 230V/60HZ

Cooling capacity: 519W

Input Power Watts: 400 W

Power: 1/3 HP

Description rapide

Condition:	Nouveau	Type:	Piston
Configuration:	Stationnaire	Source d'énergie:	Alimentation AC
Modèle de lubrifica...	Lubrifié	Muet:	Oui
Point d'origine:	Guangdong, China	Marque nom:	tecumseh
Numéro de Type:	CAE4448Y	Tension:	208 ~ 220V/1PH/50HZ
Dimension (L*W*H):	1 unité	Poids:	20kg
Certification:	ROHS	Garantie:	1 année
Service après-vente...	Aucun service d'outre-mer fourni	Gaz:	R134a
Chevaux:	1/3HP		

Private Picture Copyright: WWW.MBSM.PRO

Compressors	Displacement CC	Motor	Cooling capacity (Watt) EN12900 condensing T° +45°C , subcooling 0K, Return Gas 20°C							EN12900 evaporating T° -10°C		Weight Kg
			evaporating T°							Power input(Watt)	COP (W/W)	
			-15	-10	-5	0	5	10	15			
AE4425Y	6,69	CSIR	266	342	424	519	633	770	938	199	1,72	9,1
AEZ4425Y	7,6	CSIR	239	320	414	522	641	771	912	205	1,56	9,7
											9%	
AE4430Y	8,02	CSIR	254	382	488	613	760	930	1127	237	1,61	9,4
AEZ4430Y	8,8	CSIR	316	404	512	639	784	946	1122	258	1,57	10,2
											3%	
AE4440Y	10,33	CSIR	399	508	637	790	968	1176	1417	302	1,68	9,6
CAE4440Y	12	CSIR	399	519	666	837	1033	1250	1489	342	1,52	10,8
											10%	
AE4450Y	13,24	CSIR	526	672	843	1042	1273	1540	1847	370	1,82	10,5
CAE4448Y	14,2	CSIR	519	654	822	1023	1253	1512	1797	400	1,64	11,9
											10%	
AE4456Y	14,51	CSIR	579	737	921	1133	1380	1664	1990	424	1,74	11
CAE4456Y	16	CSIR	590	744	933	1156	1411	1695	2006	486	1,53	12,5
											12%	
AE4460Y	15,09	CSR	597	766	958	1181	1437	1732	2070	409	1,87	11,3

Private Picture Copyright: WWW.MBSM.PRO

Basic Info.

Model NO.	CAE4448Y	Refrigerant Type	Ammonia
Refrigerant	R134A	Voltage	208V/50Hz 230V/60Hz
Horsepower	1/3HP	Capacity(W)	519W
Input Power(Kw)	400W	Oil Charge (Cm3)	450
Net Weight(Kg)	12kg	Cop(W/W)	1.64
Trademark	tecumseh	Transport Package	Wooden Box
Specification	208V/50HZ 230V/60HZ	Origin	France
HS Code	8414309010		

Private Picture Copyright: WWW.MBSM.PRO

Mbsm.pro, Donper, Hermetic, Compressor , R600a, Lj126Cy, lu126cy1, 1/3 Hp, R600a

written by Lilianne | 6 April 2021



Mbsm.pro, Donper, Hermetic, Compressor , R600a, Lj126Cy,
lu126cy1, 1/3 Hp, R600a