

**Mbsm.pro, compressor,
MT160HW4D , 13 hp, MT160,
Displacement: 271.55cm³/rev**

written by Lilianne | 30 August 2022

*Mbsm.pro, Danfoss, Compressor, MT100HS4D, 8.3HP, R22, 380V,
3PH*

Danfoss Commercial Compressors



Model no: MT160HW4EVE

MADE IN FRANCE



380-400V 3- 50 Hz UL electrical ratings

460V 3- 60 Hz

LR 130A 36A MAX


Serial no: EF1007049041




THERMALLY PROTECTED

P.E.D. Marking	LP side	HP side
PS	18.4 bar	27.8 bar
TS max	50 °C	68 °C
TS min	-35 °C	-35 °C
Volume	31 l	1.2 l

Lubricant: MINERAL OIL 160 P



Refrigerant: R22(ULrating)-R417A with 160PZ



WARNING

Installation and servicing must be performed by trained personnel. Read the instructions of the safety warning card before starting any work. Do not use the compressor if it is damaged or if it is not working properly. Do not touch the compressor if it is hot. Do not touch the compressor if it is running. Do not touch the compressor if it is under pressure. Do not touch the compressor if it is under vacuum. Do not touch the compressor if it is under high pressure. Do not touch the compressor if it is under low pressure. Do not touch the compressor if it is under high vacuum. Do not touch the compressor if it is under low vacuum. Do not touch the compressor if it is under high pressure. Do not touch the compressor if it is under low pressure. Do not touch the compressor if it is under high vacuum. Do not touch the compressor if it is under low vacuum.



CAUTION

Use only manufacturer's approved refrigerants, lubricants and electrical components. Improper use of refrigerant / lubricant / electrical components could cause fire, explosion, electric shock, etc. For details, refer to the safety warning card and the instructions of the manufacturer. Distributor network at <http://www.maneurop.com>.



Danfoss Commercial Compressors



Model no: MT160HW4EVE



Serial no: EF1007049041



MADE IN FRANCE
380-400V 3~ 50 Hz
460V 3~ 60 Hz
LR 130A
36A MAX
UL electrical ratings

THERMALLY PROTECTED

P.E.D.

Marking	LP side	HP side
PS	18.4 bar	27.8 bar
TS max	50 °C	68 °C
TS min	-35 °C	-35 °C
Volume	31 l	1.2 l

Lubricant: MINERAL OIL 160 P




Refrigerant: R22(ULrating)-R417A with 160PZ



WARNING

Installation and servicing shall be performed by trained personnel only. Failure to observe these safety warnings could result in serious injury or death.
Read the instructions carefully before starting the compressor. Turn off power before servicing the compressor.
Do not touch the compressor when it is running. The compressor is hot and may cause burns.
Do not touch the compressor when it is running. The compressor is hot and may cause burns.
Do not touch the compressor when it is running. The compressor is hot and may cause burns.
Do not touch the compressor when it is running. The compressor is hot and may cause burns.



CAUTION

Use only manufacturer's approved refrigerants, lubricants and electrical components. Unauthorized refrigerant / lubricant / electrical components could cause fire, explosion, electrical shocking.
For details, refer to multi language instructions and see Parts & accessories section available on Danfoss website at <http://www.danfoss.com>.