

# Compressor, hermetic, medium temperature, 7 HP, r22, POE, MT80HP4, MT80 HP4, 400/3/50, 460/3/60 volt, 1-3/4" RL – 1-1/8" x 1-1/4" RL – 3/4"

written by Lilianne | 11 December 2021

## Product details

<b>Gross weight</b>	41.58 kg
<b>Net weight</b>	39.1 kg
<b>EAN</b>	5702428839525

<b>Approval standard</b>	CE UL
<b>Brand technique</b>	Reciprocating compressor
<b>Capacity control</b>	Fixed speed
<b>Colour</b>	Blue
<b>Compressor power supply [V/Ph/Hz]</b>	400/3/50 460/3/60
<b>Configuration code</b>	Single
<b>Connection type</b>	Rotolock
<b>Cylinder</b>	2
<b>Description</b>	MT080-4
<b>Diameter [mm]</b>	288 mm

<b>Discharge connection height [mm]</b>	74 mm
<b>Discharge connection mounting torque [Nm]</b>	90 Nm
<b>Discharge connection pipe size [in]</b>	3/4 in
<b>Discharge connection rotolock size [in]</b>	1 1/4 in
<b>Discharge connection size [in]</b>	1 1/4 in
<b>Discharge connection sleeve pipe size [in]</b>	3/4 in
<b>Drawing number</b>	8502012g
<b>Economizer</b>	No
<b>Factory HP [bar]</b>	25 bar
<b>Factory LP [bar]</b>	25 bar
<b>Fitting remark</b>	(shipped with rotolock version only)
<b>Fitting sleeve</b>	ODF
<b>Fitting standard</b>	Rotolock
<b>Frequency [Hz]</b>	50/60
<b>Gauge port HP</b>	None
<b>Gauge port LP</b>	Schrader
<b>Generation code</b>	B
<b>Glass mounting</b>	Threaded
<b>Glass torque [Nm]</b>	50 Nm
<b>GP LP torque [Nm]</b>	15 Nm
<b>High side max pressure (Ps)</b>	27.8 bar
<b>High Side TS Max</b>	150 °C
<b>High Side TS Min</b>	-35 °C
<b>High Side Volume</b>	0.6 L
<b>High value of nominal voltage at 50Hz [V]</b>	400 V

<b>High value of nominal voltage at 60Hz [V]</b>	460 V
<b>High value of voltage range at 50Hz [V]</b>	460 V
<b>High value of voltage range at 60Hz [V]</b>	506 V
<b>IP protection class</b>	IP55 (with cable gland)
<b>Low side max pressure (Ps)</b>	18.4 bar
<b>Low Side TS Max</b>	50 °C
<b>Low Side TS Min</b>	-35 °C
<b>Low Side Volume</b>	16.5 L
<b>Low value of nominal voltage at 50Hz [V]</b>	380 V
<b>Low value of nominal voltage at 60Hz [V]</b>	460 V
<b>Low value of voltage range at 50Hz [V]</b>	340 V
<b>Low value of voltage range at 60Hz [V]</b>	414 V
<b>LRA</b>	80 A
<b>MCC</b>	18 A
<b>Model number</b>	MT80HP4AVE
<b>Motor protection</b>	Internal overload protector
<b>Mounting torque [Nm]</b>	15 Nm
<b>Nominal cooling capacity 60 kBTU/h</b>	80.2 kBtu/h
<b>Nominal cooling capacity at 50Hz</b>	17.8 kW
<b>Nominal cooling capacity at 60Hz</b>	23.5 kW
<b>Number of starts per hour [Max]</b>	12
<b>Oil charge [L]</b>	1.8 L
<b>Oil equalization</b>	3/8" flare SAE

<b>Oil equalization torque [Nm]</b>	30 Nm
<b>Oil reference</b>	160P
<b>Packaging height [mm]</b>	455 mm
<b>Packaging length [mm]</b>	395 mm
<b>Packaging weight [Kg]</b>	44 kg
<b>Packaging width [mm]</b>	365 mm
<b>Packing format</b>	Single pack
<b>Packing quantity</b>	1
<b>Phase</b>	3
<b>Power connections</b>	Spade
<b>Refrigerant</b>	R22
<b>Refrigerant charge [kg] [Max]</b>	5 kg
<b>Relief valve</b>	30 bar/8 bar
<b>Rotational speed at 50Hz [rpm]</b>	2900 rpm
<b>Rotational speed at 60Hz [rpm]</b>	3500 rpm
<b>Segment usage</b>	Air conditioning Refrigeration MT
<b>Shipped fittings</b>	Suction and discharge solder sleeves, rotolock nuts and gaskets
<b>Shipped instructions</b>	Installation instructions
<b>Shipped mounting</b>	Mounting kit with grommets, bolts, nuts, sleeves and washers
<b>Shipped oil</b>	Initial oil charge
<b>Suction connection height [mm]</b>	265 mm
<b>Suction connection mounting torque [Nm]</b>	110 Nm
<b>Suction connection pipe size [in]</b>	1 1/8 in

<b>Suction connection rotolock size [in]</b>	1 3/4 in
<b>Suction connection size [in]</b>	1 3/4 in
<b>Suction connection sleeve pipe size [in]</b>	1 1/8 in
<b>Swept volume [cm<sup>3</sup>]</b>	135.78 cm <sup>3</sup>
<b>Technology</b>	Reciprocating
<b>Test dif [bar] [Max]</b>	30 bar
<b>Test HP [bar] [Max]</b>	30 bar
<b>Test LP [bar] [Max]</b>	25 bar
<b>Torque earth [Nm]</b>	3 Nm
<b>Torque power [Nm]</b>	3 Nm
<b>Total height [mm]</b>	413 mm
<b>Type</b>	MT
<b>Type designation</b>	Compressor
<b>Viscosity [cP]</b>	32 cP
<b>Winding resistance for three-phase compressors with identical windings [Ohm]</b>	1.94 Ohm

Description

## Product details

<b>Gross weight</b>	44.5 kg
<b>Net weight</b>	42 kg
<b>EAN</b>	5702428839525
<b>Gross weight</b>	44.5 kg
<b>Net weight</b>	42 kg
<b>EAN</b>	5702428839525

<b>Approval standard</b>	CE UL
<b>Brand technique</b>	Reciprocating compressor
<b>Capacity control</b>	Fixed speed
<b>Colour</b>	Blue
<b>Compressor power supply [V/Ph/Hz]</b>	400/3/50 460/3/60
<b>Configuration code</b>	Single
<b>Connection type</b>	Rotolock
<b>Cylinder</b>	2
<b>Description</b>	MT080-4
<b>Diameter [mm]</b>	288 mm
<b>Discharge connection height [mm]</b>	74 mm
<b>Discharge connection mounting torque [Nm]</b>	90 N-m
<b>Discharge connection pipe size [in]</b>	3/4 in
<b>Discharge connection rotolock size [in]</b>	1 1/4 in
<b>Discharge connection size [in]</b>	1 1/4 in
<b>Discharge connection sleeve pipe size [in]</b>	3/4 in
<b>Drawing number</b>	8502012g
<b>Economizer</b>	No
<b>Factory HP [bar]</b>	25 bar
<b>Factory LP [bar]</b>	25 bar
<b>Fitting remark</b>	(shipped with rotolock version only)
<b>Fitting sleeve</b>	ODF
<b>Fitting standard</b>	Rotolock

<b>Frequency [Hz]</b>	50/60
<b>Gauge port HP</b>	None
<b>Gauge port LP</b>	Schrader
<b>Generation code</b>	B
<b>Glass mounting</b>	Threaded
<b>Glass torque [Nm]</b>	50 N-m
<b>GP LP torque [Nm]</b>	15 N-m
<b>High side max pressure (Ps)</b>	27.8 bar
<b>High Side TS Max</b>	150 Â°C
<b>High Side TS Min</b>	-35 Â°C
<b>High Side Volume</b>	0.6 L
<b>High value of nominal voltage at 50Hz [V]</b>	400 V
<b>High value of nominal voltage at 60Hz [V]</b>	460 V
<b>High value of voltage range at 50Hz [V]</b>	460 V
<b>High value of voltage range at 60Hz [V]</b>	506 V
<b>IP protection class</b>	IP55 (with cable gland)
<b>Low side max pressure (Ps)</b>	18.4 bar
<b>Low Side TS Max</b>	50 Â°C
<b>Low Side TS Min</b>	-35 Â°C
<b>Low Side Volume</b>	16.5 L
<b>Low value of nominal voltage at 50Hz [V]</b>	380 V
<b>Low value of nominal voltage at 60Hz [V]</b>	460 V
<b>Low value of voltage range at 50Hz [V]</b>	340 V

<b>Low value of voltage range at 60Hz [V]</b>	414 V
<b>LRA</b>	80 A
<b>MCC</b>	18.5 A
<b>Model number</b>	MT80HP4AVE
<b>Motor protection</b>	Internal overload protector
<b>Mounting torque [Nm]</b>	15 N-m
<b>Nominal cooling capacity 60 kBTU/h</b>	80.2 kBtu/h
<b>Nominal cooling capacity at 50Hz</b>	17.8 kW
<b>Nominal cooling capacity at 60Hz</b>	23.5 kW
<b>Number of starts per hour [Max]</b>	12
<b>Oil charge [L]</b>	1.8 L
<b>Oil equalization</b>	3/8" flare SAE
<b>Oil equalization torque [Nm]</b>	30 N-m
<b>Oil reference</b>	160P
<b>Packaging height [mm]</b>	455 mm
<b>Packaging length [mm]</b>	395 mm
<b>Packaging weight [Kg]</b>	44 kg
<b>Packaging width [mm]</b>	365 mm
<b>Packing format</b>	Single pack
<b>Packing quantity</b>	1
<b>Phase</b>	3
<b>Power connections</b>	Spade
<b>Refrigerant</b>	R22
<b>Refrigerant charge [kg] [Max]</b>	5 kg
<b>Relief valve</b>	30 bar/8 bar
<b>Rotational speed at 50Hz [rpm]</b>	2900 rpm
<b>Rotational speed at 60Hz [rpm]</b>	3500 rpm



<b>Segment usage</b>	Air conditioning Refrigeration MT
<b>Shipped fittings</b>	Suction and discharge solder sleeves, rotolock nuts and gaskets
<b>Shipped instructions</b>	Installation instructions
<b>Shipped mounting</b>	Mounting kit with grommets, bolts, nuts, sleeves and washers
<b>Shipped oil</b>	Initial oil charge
<b>Suction connection height [mm]</b>	265 mm
<b>Suction connection mounting torque [Nm]</b>	110 N-m
<b>Suction connection pipe size [in]</b>	1 1/8 in
<b>Suction connection rotolock size [in]</b>	1 3/4 in
<b>Suction connection size [in]</b>	1 3/4 in
<b>Suction connection sleeve pipe size [in]</b>	1 1/8 in
<b>Swept volume [cm<sup>3</sup>]</b>	135.78 cm <sup>3</sup>
<b>Technology</b>	Reciprocating
<b>Test dif [bar] [Max]</b>	30 bar
<b>Test HP [bar] [Max]</b>	30 bar
<b>Test LP [bar] [Max]</b>	25 bar
<b>Torque earth [Nm]</b>	3 N-m
<b>Torque power [Nm]</b>	3 N-m
<b>Total height [mm]</b>	413 mm
<b>Type</b>	MT
<b>Type designation</b>	Compressor
<b>Viscosity [cP]</b>	32 cP

<b>Winding resistance for three-phase compressors with identical windings [Ohm]</b>	1.94 Ohm
<b>Approval standard</b>	CE UL
<b>Brand technique</b>	Reciprocating compressor
<b>Capacity control</b>	Fixed speed
<b>Colour</b>	Blue
<b>Compressor power supply [V/Ph/Hz]</b>	400/3/50 460/3/60
<b>Configuration code</b>	Single
<b>Connection type</b>	Rotolock
<b>Cylinder</b>	2
<b>Description</b>	MT080-4
<b>Diameter [mm]</b>	288 mm
<b>Discharge connection height [mm]</b>	74 mm
<b>Discharge connection mounting torque [Nm]</b>	90 N-m
<b>Discharge connection pipe size [in]</b>	3/4 in
<b>Discharge connection rotolock size [in]</b>	1 1/4 in
<b>Discharge connection size [in]</b>	1 1/4 in
<b>Discharge connection sleeve pipe size [in]</b>	3/4 in
<b>Drawing number</b>	8502012g
<b>Economizer</b>	No
<b>Factory HP [bar]</b>	25 bar
<b>Factory LP [bar]</b>	25 bar
<b>Fitting remark</b>	(shipped with rotolock version only)
<b>Fitting sleeve</b>	ODF

<b>Fitting standard</b>	Rotolock
<b>Frequency [Hz]</b>	50/60
<b>Gauge port HP</b>	None
<b>Gauge port LP</b>	Schrader
<b>Generation code</b>	B
<b>Glass mounting</b>	Threaded
<b>Glass torque [Nm]</b>	50 N-m
<b>GP LP torque [Nm]</b>	15 N-m
<b>High side max pressure (Ps)</b>	27.8 bar
<b>High Side TS Max</b>	150 Â°C
<b>High Side TS Min</b>	-35 Â°C
<b>High Side Volume</b>	0.6 L
<b>High value of nominal voltage at 50Hz [V]</b>	400 V
<b>High value of nominal voltage at 60Hz [V]</b>	460 V
<b>High value of voltage range at 50Hz [V]</b>	460 V
<b>High value of voltage range at 60Hz [V]</b>	506 V
<b>IP protection class</b>	IP55 (with cable gland)
<b>Low side max pressure (Ps)</b>	18.4 bar
<b>Low Side TS Max</b>	50 Â°C
<b>Low Side TS Min</b>	-35 Â°C
<b>Low Side Volume</b>	16.5 L
<b>Low value of nominal voltage at 50Hz [V]</b>	380 V
<b>Low value of nominal voltage at 60Hz [V]</b>	460 V

<b>Low value of voltage range at 50Hz [V]</b>	340 V
<b>Low value of voltage range at 60Hz [V]</b>	414 V
<b>LRA</b>	80 A
<b>MCC</b>	18.5 A
<b>Model number</b>	MT80HP4AVE
<b>Motor protection</b>	Internal overload protector
<b>Mounting torque [Nm]</b>	15 N-m
<b>Nominal cooling capacity 60 kBTU/h</b>	80.2 kBtu/h
<b>Nominal cooling capacity at 50Hz</b>	17.8 kW
<b>Nominal cooling capacity at 60Hz</b>	23.5 kW
<b>Number of starts per hour [Max]</b>	12
<b>Oil charge [L]</b>	1.8 L
<b>Oil equalization</b>	3/8" flare SAE
<b>Oil equalization torque [Nm]</b>	30 N-m
<b>Oil reference</b>	160P
<b>Packaging height [mm]</b>	455 mm
<b>Packaging length [mm]</b>	395 mm
<b>Packaging weight [Kg]</b>	44 kg
<b>Packaging width [mm]</b>	365 mm
<b>Packing format</b>	Single pack
<b>Packing quantity</b>	1
<b>Phase</b>	3
<b>Power connections</b>	Spade
<b>Refrigerant</b>	R22
<b>Refrigerant charge [kg] [Max]</b>	5 kg
<b>Relief valve</b>	30 bar/8 bar
<b>Rotational speed at 50Hz [rpm]</b>	2900 rpm

<b>Rotational speed at 60Hz [rpm]</b>	3500 rpm
<b>Segment usage</b>	Air conditioning Refrigeration MT
<b>Shipped fittings</b>	Suction and discharge solder sleeves, rotolock nuts and gaskets
<b>Shipped instructions</b>	Installation instructions
<b>Shipped mounting</b>	Mounting kit with grommets, bolts, nuts, sleeves and washers
<b>Shipped oil</b>	Initial oil charge
<b>Suction connection height [mm]</b>	265 mm
<b>Suction connection mounting torque [Nm]</b>	110 N-m
<b>Suction connection pipe size [in]</b>	1 1/8 in
<b>Suction connection rotolock size [in]</b>	1 3/4 in
<b>Suction connection size [in]</b>	1 3/4 in
<b>Suction connection sleeve pipe size [in]</b>	1 1/8 in
<b>Swept volume [cm<sup>3</sup>]</b>	135.78 cm <sup>3</sup>
<b>Technology</b>	Reciprocating
<b>Test dif [bar] [Max]</b>	30 bar
<b>Test HP [bar] [Max]</b>	30 bar
<b>Test LP [bar] [Max]</b>	25 bar
<b>Torque earth [Nm]</b>	3 N-m
<b>Torque power [Nm]</b>	3 N-m
<b>Total height [mm]</b>	413 mm
<b>Type</b>	MT
<b>Type designation</b>	Compressor

<b>Viscosity [cP]</b>	32 cP
<b>Winding resistance for three-phase compressors with identical windings [Ohm]</b>	1.94 Ohm

Refrigerant: R22, Segment usage: Air conditioning;Refrigeration MT, Compressor power supply [V/Ph/Hz]: 400/3/50 460/3/60

## Product details

<b>Gross weight</b>	44.5 kg
<b>Net weight</b>	42 kg
<b>EAN</b>	5702428839525
<b>Gross weight</b>	44.5 kg
<b>Net weight</b>	42 kg
<b>EAN</b>	5702428839525

<b>Approval standard</b>	CE UL
<b>Brand technique</b>	Reciprocating compressor
<b>Capacity control</b>	Fixed speed
<b>Colour</b>	Blue
<b>Compressor power supply [V/Ph/Hz]</b>	400/3/50 460/3/60
<b>Configuration code</b>	Single
<b>Connection type</b>	Rotolock
<b>Cylinder</b>	2
<b>Description</b>	MT080-4
<b>Diameter [mm]</b>	288 mm

<b>Discharge connection height [mm]</b>	74 mm
<b>Discharge connection mounting torque [Nm]</b>	90 N-m
<b>Discharge connection pipe size [in]</b>	3/4 in
<b>Discharge connection rotolock size [in]</b>	1 1/4 in
<b>Discharge connection size [in]</b>	1 1/4 in
<b>Discharge connection sleeve pipe size [in]</b>	3/4 in
<b>Drawing number</b>	8502012g
<b>Economizer</b>	No
<b>Factory HP [bar]</b>	25 bar
<b>Factory LP [bar]</b>	25 bar
<b>Fitting remark</b>	(shipped with rotolock version only)
<b>Fitting sleeve</b>	ODF
<b>Fitting standard</b>	Rotolock
<b>Frequency [Hz]</b>	50/60
<b>Gauge port HP</b>	None
<b>Gauge port LP</b>	Schrader
<b>Generation code</b>	B
<b>Glass mounting</b>	Threaded
<b>Glass torque [Nm]</b>	50 N-m
<b>GP LP torque [Nm]</b>	15 N-m
<b>High side max pressure (Ps)</b>	27.8 bar
<b>High Side TS Max</b>	150 Â°C
<b>High Side TS Min</b>	-35 Â°C
<b>High Side Volume</b>	0.6 L
<b>High value of nominal voltage at 50Hz [V]</b>	400 V

<b>High value of nominal voltage at 60Hz [V]</b>	460 V
<b>High value of voltage range at 50Hz [V]</b>	460 V
<b>High value of voltage range at 60Hz [V]</b>	506 V
<b>IP protection class</b>	IP55 (with cable gland)
<b>Low side max pressure (Ps)</b>	18.4 bar
<b>Low Side TS Max</b>	50 Â°C
<b>Low Side TS Min</b>	-35 Â°C
<b>Low Side Volume</b>	16.5 L
<b>Low value of nominal voltage at 50Hz [V]</b>	380 V
<b>Low value of nominal voltage at 60Hz [V]</b>	460 V
<b>Low value of voltage range at 50Hz [V]</b>	340 V
<b>Low value of voltage range at 60Hz [V]</b>	414 V
<b>LRA</b>	80 A
<b>MCC</b>	18.5 A
<b>Model number</b>	MT80HP4AVE
<b>Motor protection</b>	Internal overload protector
<b>Mounting torque [Nm]</b>	15 N-m
<b>Nominal cooling capacity 60 kBTU/h</b>	80.2 kBtu/h
<b>Nominal cooling capacity at 50Hz</b>	17.8 kW
<b>Nominal cooling capacity at 60Hz</b>	23.5 kW
<b>Number of starts per hour [Max]</b>	12
<b>Oil charge [L]</b>	1.8 L
<b>Oil equalization</b>	3/8" flare SAE



<b>Oil equalization torque [Nm]</b>	30 N-m
<b>Oil reference</b>	160P
<b>Packaging height [mm]</b>	455 mm
<b>Packaging length [mm]</b>	395 mm
<b>Packaging weight [Kg]</b>	44 kg
<b>Packaging width [mm]</b>	365 mm
<b>Packing format</b>	Single pack
<b>Packing quantity</b>	1
<b>Phase</b>	3
<b>Power connections</b>	Spade
<b>Refrigerant</b>	R22
<b>Refrigerant charge [kg] [Max]</b>	5 kg
<b>Relief valve</b>	30 bar/8 bar
<b>Rotational speed at 50Hz [rpm]</b>	2900 rpm
<b>Rotational speed at 60Hz [rpm]</b>	3500 rpm
<b>Segment usage</b>	Air conditioning Refrigeration MT
<b>Shipped fittings</b>	Suction and discharge solder sleeves, rotolock nuts and gaskets
<b>Shipped instructions</b>	Installation instructions
<b>Shipped mounting</b>	Mounting kit with grommets, bolts, nuts, sleeves and washers
<b>Shipped oil</b>	Initial oil charge
<b>Suction connection height [mm]</b>	265 mm
<b>Suction connection mounting torque [Nm]</b>	110 N-m
<b>Suction connection pipe size [in]</b>	1 1/8 in

<b>Suction connection rotolock size [in]</b>	1 3/4 in
<b>Suction connection size [in]</b>	1 3/4 in
<b>Suction connection sleeve pipe size [in]</b>	1 1/8 in
<b>Swept volume [cm<sup>3</sup>]</b>	135.78 cm <sup>3</sup>
<b>Technology</b>	Reciprocating
<b>Test dif [bar] [Max]</b>	30 bar
<b>Test HP [bar] [Max]</b>	30 bar
<b>Test LP [bar] [Max]</b>	25 bar
<b>Torque earth [Nm]</b>	3 N-m
<b>Torque power [Nm]</b>	3 N-m
<b>Total height [mm]</b>	413 mm
<b>Type</b>	MT
<b>Type designation</b>	Compressor
<b>Viscosity [cP]</b>	32 cP
<b>Winding resistance for three-phase compressors with identical windings [Ohm]</b>	1.94 Ohm
<b>Approval standard</b>	CE UL
<b>Brand technique</b>	Reciprocating compressor
<b>Capacity control</b>	Fixed speed
<b>Colour</b>	Blue
<b>Compressor power supply [V/Ph/Hz]</b>	400/3/50 460/3/60
<b>Configuration code</b>	Single
<b>Connection type</b>	Rotolock
<b>Cylinder</b>	2
<b>Description</b>	MT080-4

<b>Diameter [mm]</b>	288 mm
<b>Discharge connection height [mm]</b>	74 mm
<b>Discharge connection mounting torque [Nm]</b>	90 N-m
<b>Discharge connection pipe size [in]</b>	3/4 in
<b>Discharge connection rotolock size [in]</b>	1 1/4 in
<b>Discharge connection size [in]</b>	1 1/4 in
<b>Discharge connection sleeve pipe size [in]</b>	3/4 in
<b>Drawing number</b>	8502012g
<b>Economizer</b>	No
<b>Factory HP [bar]</b>	25 bar
<b>Factory LP [bar]</b>	25 bar
<b>Fitting remark</b>	(shipped with rotolock version only)
<b>Fitting sleeve</b>	ODF
<b>Fitting standard</b>	Rotolock
<b>Frequency [Hz]</b>	50/60
<b>Gauge port HP</b>	None
<b>Gauge port LP</b>	Schrader
<b>Generation code</b>	B
<b>Glass mounting</b>	Threaded
<b>Glass torque [Nm]</b>	50 N-m
<b>GP LP torque [Nm]</b>	15 N-m
<b>High side max pressure (Ps)</b>	27.8 bar
<b>High Side TS Max</b>	150 Â°C
<b>High Side TS Min</b>	-35 Â°C
<b>High Side Volume</b>	0.6 L

<b>High value of nominal voltage at 50Hz [V]</b>	400 V
<b>High value of nominal voltage at 60Hz [V]</b>	460 V
<b>High value of voltage range at 50Hz [V]</b>	460 V
<b>High value of voltage range at 60Hz [V]</b>	506 V
<b>IP protection class</b>	IP55 (with cable gland)
<b>Low side max pressure (Ps)</b>	18.4 bar
<b>Low Side TS Max</b>	50 Â°C
<b>Low Side TS Min</b>	-35 Â°C
<b>Low Side Volume</b>	16.5 L
<b>Low value of nominal voltage at 50Hz [V]</b>	380 V
<b>Low value of nominal voltage at 60Hz [V]</b>	460 V
<b>Low value of voltage range at 50Hz [V]</b>	340 V
<b>Low value of voltage range at 60Hz [V]</b>	414 V
<b>LRA</b>	80 A
<b>MCC</b>	18.5 A
<b>Model number</b>	MT80HP4AVE
<b>Motor protection</b>	Internal overload protector
<b>Mounting torque [Nm]</b>	15 N-m
<b>Nominal cooling capacity 60 kBTU/h</b>	80.2 kBtu/h
<b>Nominal cooling capacity at 50Hz</b>	17.8 kW
<b>Nominal cooling capacity at 60Hz</b>	23.5 kW
<b>Number of starts per hour [Max]</b>	12

<b>Oil charge [L]</b>	1.8 L
<b>Oil equalization</b>	3/8" flare SAE
<b>Oil equalization torque [Nm]</b>	30 N-m
<b>Oil reference</b>	160P
<b>Packaging height [mm]</b>	455 mm
<b>Packaging length [mm]</b>	395 mm
<b>Packaging weight [Kg]</b>	44 kg
<b>Packaging width [mm]</b>	365 mm
<b>Packing format</b>	Single pack
<b>Packing quantity</b>	1
<b>Phase</b>	3
<b>Power connections</b>	Spade
<b>Refrigerant</b>	R22
<b>Refrigerant charge [kg] [Max]</b>	5 kg
<b>Relief valve</b>	30 bar/8 bar
<b>Rotational speed at 50Hz [rpm]</b>	2900 rpm
<b>Rotational speed at 60Hz [rpm]</b>	3500 rpm
<b>Segment usage</b>	Air conditioning Refrigeration MT
<b>Shipped fittings</b>	Suction and discharge solder sleeves, rotolock nuts and gaskets
<b>Shipped instructions</b>	Installation instructions
<b>Shipped mounting</b>	Mounting kit with grommets, bolts, nuts, sleeves and washers
<b>Shipped oil</b>	Initial oil charge
<b>Suction connection height [mm]</b>	265 mm

<b>Suction connection mounting torque [Nm]</b>	110 N-m
<b>Suction connection pipe size [in]</b>	1 1/8 in
<b>Suction connection rotolock size [in]</b>	1 3/4 in
<b>Suction connection size [in]</b>	1 3/4 in
<b>Suction connection sleeve pipe size [in]</b>	1 1/8 in
<b>Swept volume [cm3]</b>	135.78 cm3
<b>Technology</b>	Reciprocating
<b>Test dif [bar] [Max]</b>	30 bar
<b>Test HP [bar] [Max]</b>	30 bar
<b>Test LP [bar] [Max]</b>	25 bar
<b>Torque earth [Nm]</b>	3 N-m
<b>Torque power [Nm]</b>	3 N-m
<b>Total height [mm]</b>	413 mm
<b>Type</b>	MT
<b>Type designation</b>	Compressor
<b>Viscosity [cP]</b>	32 cP
<b>Winding resistance for three-phase compressors with identical windings [Ohm]</b>	1.94 Ohm









Private Picture Copyright : WWW.MBSM.PRO

Mbsm\_dot\_pro\_private\_PDF\_MTZ80HP4-1Télécharger

Mbsm\_dot\_pro\_private\_PDF\_MTZ80HP4Télécharger

Compresseur à piston Danfoss Maneurop MT22JC5PVE (2.0HP / 1PH)  
Compresseur à piston Danfoss Maneurop MT22JC4AVE (2.0HP / 3PH)  
Compresseur à piston Danfoss Maneurop MT28JC5PVE (2.3HP / 1PH)  
Compresseur à piston Danfoss Maneurop MT22JC4AVE (2.0HP / 3PH)  
Compresseur à piston Danfoss Maneurop MT28JC5PVE (2.3HP / 1PH)  
Compresseur à piston Danfoss Maneurop 3PH (2.3HP / 1PH) 2.6HP / 1PH)  
Compresseur à piston Danfoss Maneurop MT32JF4DVE (2.6HP / 3PH);  
Compresseur à piston Danfoss Maneurop MT36JG5CVE (3.0HP / 1PH)  
Compresseur à piston Danfoss Maneurop MT36JG4FVE (3.0HP / 3PH)  
Compresseur à piston Danfoss Maneurop MT40JH4EVE (3.3HP / 3PH)  
Danfoss Maneurop Compresseur à piston MT36JG4FVE (3.0HP / 3PH)  
Compresseur à piston Danfoss Maneurop MT40JH4EVE (3.3HP / 3PH)  
Danfoss Maneurop Compresseur à piston MT36JG4FVE (3.0HP / 3PH)  
Compresseur à piston Danfoss Maneurop MT40JH4EVE (3.3HP / 3PH)  
Compresseur à piston Danfoss Maneurop 3KFHB4

(3.6PH) 4.0HP / 3PH) Compresseur à piston Danfoss Maneurop MT56HL4BVE (4. 6HP / 3PH) Compresseur à piston Danfoss Maneurop MT64HM4DVE (5.3HP / 3PH) Compresseur à piston Danfoss Maneurop MT72HN4AVE (6.0HP / 3PH) Compresseur à piston Danfoss Maneurop MT80HP4AVE (6.6HP / 3PH) Compresseur à piston Danfoss Maneurop MT72HN4AVE (6.0HP / 3PH) Compresseur à piston Danfoss Maneurop MT80HP4AVE (6.6HP / 3PH) Compresseur à piston Danfoss Maneurop4.0 Compresseur à piston MT144HV4AVE (12,0HP / 3PH) Compresseur à piston Danfoss Maneurop MT160HW4EVE (13.3HP / 3PH) Compresseur à piston Danfoss Maneurop MTZ22JC5VE (2.0HP / 1PH); [R134A, R404] Compresseur à piston Danfoss Maneurop MTZ22JC4AVE (2.0HP / 3PH); [R134A, R404] Compresseur à piston Danfoss Maneurop MTZ28JE5AVE (2,3 HP / 1PH); [R134A, R404] Compresseur à piston Danfoss Maneurop MTZ28JE4AVE (2,3 HP / 3PH); [R134A, R404] Compresseur à piston Danfoss Maneurop MTZ32JF5AVE (2,6 CV / 1PH); [R134A, R404] Compresseur à piston Danfoss Maneurop MTZ32JF4BVE (2.6HP / 3PH); [R134A, R404] Compresseur à piston Danfoss Maneurop MTZ36JG5AVE (3.0HP / 1PH); [R134A, R404] Compresseur à piston Danfoss Maneurop MTZ36JG4BVE (3.0HP / 3PH); [R134A, R404] Compresseur à piston Danfoss Maneurop MTZ40JH4AVE (3,3 CV / 3PH); [R134A, R404] Compresseur à piston Danfoss Maneurop MTZ50HK4CVE (4,0 CV / 3PH); [R134A, R404] Compresseur à piston Danfoss Maneurop MTZ56HL4BVE (4,6 CV / 3PH); [R134A, R404] Compresseur à piston Danfoss Maneurop MTZ64HM4CVE (5,3 HP / 3PH); [R134A, R404] Compresseur à piston Danfoss Maneurop MTZ72HN4AVE (6,0 CV / 3PH); [R134A, R404] Compresseur à piston Danfoss Maneurop MTZ80HP4AVE (6,6 CV / 3PH); [R134A, R404] Compresseur à piston Danfoss Maneurop MTZ100HS4VE (8,3 CV / 3 PH); [R134A, R404] Compresseur à piston Danfoss Maneurop MTZ125HU4VE (10.0HP / 3PH); [R134A, R404] Compresseur à piston Danfoss Maneurop MTZ144HV4AVE (12,0 HP / 3PH); [R134A, R404] Compresseur à piston Danfoss Maneurop MTZ160HE4AVE (13,3 HP / 3PH); [R134A, R404] Compresseur à piston Danfoss Maneurop NTZ048A4LR1A (2.0HP / 3PH); [R134A, R404, R507] Compresseur à piston Danfoss Maneurop NTZ068A4LR1A (3,5 CV / 3PH); [R134A, R404, R507] Compresseur à piston Danfoss Maneurop NTZ096A4LR1A (4,5

CV / 3PH); [R134A, R404, R507] Compresseur à piston Danfoss  
Maneurop NTZ108A4LR1A (5,0 CV / 3PH); [R134A, R404, R507]  
Compresseur à piston Danfoss Maneurop NTZ136A4LR1A (6,5 CV /  
3PH); [R134A, R404, R507] Compresseur à piston Danfoss  
Maneurop NTZ215A4LR1A (10,0 HP / 3PH); [R134A, R404, R507]  
Compresseur à piston Danfoss Maneurop NTZ271A4LR1A (13.0HP /  
3PH); [R134A, R404, R507] COMPRESSEUR MANEUROP 2.0HP MT22  
MANEUROPE 2.0HP MT22 COMPRESSEUR MANEUROP COMPRESSEUR  
MTZ-22JE-4VE R404A MANEUROPE 2.30HP MT28JE-5PVE MT28-5VI /  
MT28-5VM COMPRESSEUR MANEUROP 2.30HP MT28JE-5PVE MT28-5VI /  
MT28-5VM COMPRESSEUR MANEUROPEUR 2.30H5 / R404A) COMPRESSEUR  
MANEUROP 2.8HP MTZ32-5VM (R134a / R404A / R507) COMPRESSEUR  
MANEUROP MT32JF5MVE 2-3 / 4HP ((R22) COMPRESSEUR MANEUROP  
3.0HP MT36JG4FVE (MT36-4VI / MT36-4VM) (R22) COMPRESSEUR 3.0HP  
COMPRESSEUR MT36 MANEUROP 3.3HP MT40JH4EVE COMPRESSEUR  
MANEUROP 3.3HP MTZ40-JH4AVE COMPRESSEUR (R407A / C / F / R134A  
/ R404A / R507) Compresseur MANEUROP MTZ-36-JG4AVE (R407C /  
R134a / R404A-R407C / R134a / R404A) -Compresseur JH4AVE  
(R134a / R404A) – Compresseur 3.3HP 3PH MANEUROP MTZ-44-HJ4AVE  
(R134a / R404A) – 3. 5HP 3PH MANEUROP 4HP MTZ-50HK-4CVE  
(MTZ50-4VI / MTZ50-4VM) COMPRESSEUR (R134A / R404A) MANEUROP  
MTZ56HL3BVE R407c, R134a, R507a, R404a compresseur MANEUROP  
MT-64-4VM COMPRESSEUR MANEUR 64-4VM COMPRESSEUR MANEUR  
COMPRESSEUR MT72-4VM COMPRESSEUR MANEUROP MT-80-4VM (6.5HP)  
Compresseur MANEUROP 6.6HP MT81HP4AVE COMPRESSEUR MANEUROP  
MTZ80HM4DVE COMPRESSEUR MANEUROP 8.5HP MT100-4VM COMPRESSEUR  
MANEUROPE 10HP MT100-4VM (MT100HS4DVE) COMPRESSEUR 10HP  
MT100-4VM (MT100HS4DVE) COMPRESSEUR MT12M10 MANHOP 4-  
COMPRESSEUR 10HP R22) COMPRESSEUR MANEUROP 10HP MTZ125HW4AVE  
(R404A / R134A / R507 / R407C) COMPRESSEUR MANEUROPE 12HP  
MT144-4VM COMPRESSEUR MANEUROPE 13.3HP MT160-4VM (MT160HW4DVE)  
COMPRESSEUR MANZVMER 10 COMPRESSEUR MANZVM4 (MT160HW4DVE) / 2  
' ) SER. KIT POUR MT-28 MANEUROP 7703009 (1-1 / 8 '& 3/4') SER.