

Mbsm.pro, Climatiseur, MSAGB-12HRN1-Q, 12000 Btu/h, R410a, 300g, Chaud et froid, 5 fils, T1 (Méditerranée), 1 phase, 220 V, 8.4 A

Category: expertise

written by Lilianne | 13 April 2022

Midea

⚠ PRUDENCE

1- VEILLEZ A EVACUER L'AIR A L'INTERIEUR DE L'UNITE INTERIEUR ET LES TUYAUX AVEC POMPE A VIDE

ATTENTION A LA QUANTITES ADDITIONNEL DE

CEX مبرد ذو نظام سبليت

MSAGB-12HRN1-Q	النموذج
MSAGB-12HRN1-Q	نموذج الوحدة الداخلية
MSAGB-12HRN1-Q	نموذج الوحدة الخارجية
3224 واط	قدرة التبريد
3341 واط	قدرة التسخين
R410A/1.03KG	غاز التبريد
4.2 ميغا باسكال	الضغط الأقصى
4.2 ميغا باسكال	ضغط العمل المفرط
الادفع	
1.5 ميغا باسكال	الامتصاص
220-240ف, 50هرتز	التواتر الاسمي
وحيد المراحل	
8.4 أمبير	التيار الاسمي
1850 واط	استطاعة الاستهلاك الاسمية
IP24	درجة مقاومة الوحدة الخارجية
يحتوي على غاز نو مفعول مفلور	
امكانية الحثراز العالمي 2088	
ما يعادل 2.15 طن من CO2	

Midea

Mbsm.pro, Climatiseur, MSAGB-12HRN1-Q, 12000 Btu/h, R410a, 300g, Chaud et froid, 5 fils, T1 (Méditerranée), 1 phase, 220 V, 8.4 A

**Mbsm.pro, Compressor, Copeland,
Scroll, ZP90KCE-TFD-425, R410A,
380V*3, 50Hz, 7.5 Hp++, 74.500 Btu/h,
HBP**

Category: compressor

written by Lilianne | 13 April 2022



Private Picture Copyright: WWW.MBSM.PRO

Mbsm.pro, Compressor, Copeland, Scroll, ZP90KCE-TFD-425, R410A, 380V*3, 50Hz, 7.5 Hp++, 74.500 Btu/h, HBP

Mbsm.pro, Air conditioner,
Tac-36ch5a, 36000 Btu, 17 a,
Compressor, ATH420MV, ATH420MV-C9EU,
Hitachi Compressor, 4hp, R410a, 2.5
kg, 10060 W, 220V 220-240, 50Hz, 1 PH

Category: air conditioner,compressor
written by Lilianne | 13 April 2022



Private Picture Copyright: WWW.MBSM.PRO

Mbsm.pro, Air conditioner, Tac-36ch5a, 36000 Btu, 17 a, Compressor, ATH420MV,
ATH420MV-C9EU, Hitachi Compressor, 4hp, R410a, 2.5 kg, 10060 W, 220V 220-240,
50Hz, 1 PH

Mbsm.pro, Gree, air conditioner,
GWHD(14)NK6L0(LC)(LH), GWHD(14)NK6L0,
CB228W08401, CB228W08400, 14000 btu,

Inverter Rotary, Compressor, QXA-B141zF030A, 2 hp-, 1440 w, I_{ra} 25 A, DC block controller, r410a, 220 v, 50 hz, 900 to 7200 RPM

Category: air conditioner,compressor
written by Lilianne | 13 April 2022

TOSOT

QXA-B141zF030E

260-350V 900-7200rpm R410A



LDB42DA428H0503

ZHUHAI LANDA COMPRESSOR CO., LTD.

Mbsm.pro, GRee, air conditioner, GWHD(14)NK6L0(LC)(LH), GWHD(14)NK6L0, CB228W08401, CB228W08400, 14000 btu, Inverter Rotary, Compressor, QXA-B141zF030A, 2 hp-, 1440 w, lra 25 A, DC block controller, r410a, 220 v, 50 hz, 900 to 7200 RPM

Mbsm.pro, Toshiba, Compressor, R410A, PA235G2CS-4KTM1, 2.5 hp, 19931 btu , 1.6 Ton, 1935 w PA235G2CS, 4KTM1, r410a, T3 rotary compressor, PA206G2C-4KTL, PA225G2C-3MT, PA235G2CS-4KTM1

Category: compressor

written by Lilianne | 13 April 2022

Mbsm.pro, Toshiba, Compressor, 2.5 hp, PA235G2CS-4KTM1, 2.5 hp, 19931 btu , 1935 w PA235G2CS, 4KTM1, r410a, T3 rotary compressor, PA206G2C-4KTL, PA225G2C-3MT, PA235G2CS-4KTM1

HGX12P/75-4, R410A, compressor, semi-hermétique, BOCK, 25,0 hp

Category: Chaud&Froid,compressor

written by Lilianne | 13 April 2022

HGX12P/75-4 R410A

Data Sheet

Power supply	220/240 V-380/420 V-50 Hz-3 ph (265/290 V-440/480 V-60 Hz-3 ph) Δ Y
Horsepower	25,0 hp
Displacement	6,70 m3
Cooling capacity at Refrigeration conditions, R407C	3,39 kW
Cooling capacity at Refrigeration conditions, R404A	3,97 kW
Refrigerant	R134a, R404A, R407C, R407F, R448A, R449A, R507, R513A
Suction pipe	5/8"
Discharge pipe	1/2"
Weight	49 kg
LRA (Δ/y)	43/25 A
MCC (Δ/y)	8,0/4,6 A

Type of oil	FUCHS Reniso Triton SE 55
Other remarks	Available in ATEX version, Electronic frequency control (30-70 Hz), Equipped with oil pump without connections to the differential oil pressure switch
Accessories	Control Capacity 50/100%, Crankcase heater 50-120 W, Thermal protection thermostat (PTC sensor)
Application	MHBP
Technology	Fixed speed
Lubrication mode	Oil pump
Low pressure design	19 bar
High pressure design	28 bar
Type of motor cooling	Suction gas
Protection type	IP 66
Motor protection type	INT69 G
Speed	1450 rpm



Mbsm_dot_pro_private_PDF_HGX12PTélécharger



BOCK BOCK GmbH, Benzstr.7 CE
72636 Frickenhausen, Germany

Typ: HGX12P/75-4 S

Nr.: BD44874A046

I_{max}: 8,0/4,6A

I_{block} Δ: 43A Y: 25A

P_{max}: ND(LP) / HD(HP) = 19/28 bar

220-240VΔ/380-420VY - 3 - 50HZ

n: 1450 min⁻¹ V_{th}: 6,70 m³/h

265-290VΔ/440-480VY - 3 - 60HZ

n: 1740 min⁻¹ V_{th}: 8,1 m³/h

IP66

Öl: BOCKlubE55

Import

Ab 02. August 2021 sind
Diese Änderung ist auch an
Die im Werk serienmäßig eingefüllte
Wartungseinheiten eingesetzt werden
aufgrund der Verwendung minderwertiger
erheblich abweichen und zudem Probleme
insbesondere eine Validierung im gesamten
Ölen nicht gewährleistet. Aus diesem Grund
Für durch alternative Öle entstandene Schäden

Kältemittel
HFKW / HFO
CO₂ / HFO
HFCKW
Kohlenwasserstoffe

Typschild Beispiel:
Name plate example: