Mbsm.pro, Compressor, ASF852HG, ROHS, 850 w, R134a, 1/4 hp++, 1/3 hp-, Hbp, relative, Aspera NEK6170Z

written by Lilianne | 11 March 2024



Mbsm.pro, Compressor, ASF852HG, ROHS, 850 w, R134a, 1/4 hp++, 1/3 hp-, Hbp

High, Efficiency, R134a, Hermetic, Compressor, GPY16AF, RoHS, 3/8hp, csir, lbp, 220v, 380w

written by Lilianne | 11 March 2024

R134a GPY16AF series sealed refrigeration compressor 220-240v/50Hz

The main feature:
strong loading capacity,
high efficiency,
low noise,
light vibration,
good reliability.

suitable for mid-size refrigerators, freezers, displayers, beer displayers and other mid-size refrigeration appliances.

The structure form is hermetical crank connecting-rod reciprocating piston type.

They are the best selling high-tech compressors sold in the world. They are ideal for domestic refrigeration and also for small commercial applications. They are small, have low noise and vibration levels, they achieve the highest levels of efficiency available in the market for this category.

KONOR	Displ.	power	Motor type	V/Hz	Cooling Capacity W	Net Weight KG
GQR60AA	6	1/6	RSIR	220-240V/50Hz	140	9.4
GQR70AA	6.6	1/5	RSIR	220-240V/50Hz	165	9.4
GQR80AA	8.1	1/4	RSIR	220-240V/50Hz	198	9.4
GQR90AA	9.1	1/4	RSIR	220-240V/50Hz	220	10.1
GQY99AA	9.9	1/4	RSIR	220-240V/50Hz	270	10.9
GQY12AF	11.8	1/3	CSIR	220-240V/50Hz	325	10.56
GQY16AF	16.2	3/8	CSIR	220-240V/50Hz	380	12.1
GP16MG	16.2	5/8	CSIR	220-240V/50Hz	870	12.5
GP12MG	11.8	5/8	CSIR	220-240V/50Hz	656	10.9
GP12TG	11.8	3/8	CSIR	220-240V/50Hz	1140	11.8

GQR80TG	8.1	1/4	CSIR	220-240V/50Hz	730	9.8
GQR90TG	9.1	1/4	CSIR	220-240V/50Hz	830	10.5
GQR60TG	6	1/5	CSIR	220-240V/50Hz	520	9.8

Specification

Hermetic motor driven the piston connecting rod type compressor. With relay start-up of hammer type, and equipped with overload protector.

Application

Widely used in homeand commercial refrigerator, air-curtain cabinet, display showcase, ice maker, chiller freezer, dehumidifier, etc.

R134a LBP Fan Cooling Compressor

Model: GPY16AF

Power:3/8HP

Displacement:16.2cm3

Capacity:380w

COP:1.3W

Voltage:200-240V/50HZ

Motor Way:CSIR

Application:LBP

Cooling Type:Fan Cooling

Height:210mm

Net Weight:12.9kg

Dimension:210*162*237.2(mm)

Test Conditions(ASHRAE)

Evaporating temperature -23	3.3ºC					
Condensing temperature 54	.4ºC					
Subcooling temperature 32	.2ºC					
Suction temperature 32.2	o C					
Ambient temperature 32.2	ō C					
Conversion:						
1watt=3.41Btu/h=0.86kcal/h						



Compressor, ROHS, 1/3HP, R134A, Tecumseh, CAE4448Y, HBP, 208V/50HZ 230V/60HZ

written by Lilianne | 11 March 2024



Basic Info.

Model NO. CAE4448Y Refrigerant Type Ammonia

Refrigerant

R134A

Voltage

208V/50Hz 230V/60Hz

Horsepower

1/3HP

Capacity(W)

519W

Input Power(Kw)

400W

Oil Charge (Cm3)

450

Net Weight(Kg)

12kg

Cop(W/W)

1.64

Trademark

tecumseh

Transport Package

Wooden Box

Specification

208V/50HZ 230V/60HZ

Origin

France

HS Code

8414309010

1/3HP HBP Original Made in France R134A Tecumseh Compressor CAE4448Y Refrigerator Compressor For

Refrigerator/Showcase/Cold Room

Product Description

Model: CAE4448Y

Brand : Tecumseh

Type: hermetic

Refrigerant: R134A

Voltage: 208V/50HZ 230V/60HZ

Cooling capacity: 519W

Input Power Watts: 400 W

Power: 1/3 HP

Description rapide

 Condition:
 Nouveau
 Type:
 Piston

 Configuration:
 Stationnaire
 Source d'énergie:
 Alimentation AC

Modèle de lubrifica... Lubrifié Muet: Oui

Point d'origine: Guangdong, China Marque nom: tecumsel

Numéro de Type: CAE4448Y Tension: $208 \sim 220V/1PH/50HZ$

 Dimension (L*W*H): 1 unité
 Poids:
 20kg

 Certification:
 ROHS
 Garantie:
 1 année

 Service après-vente...Aucun service d'outre-mer fourni
 Gaz:
 R134a

Chevaux: 1/3HP

Private Picture Copyright: WWW.MBSM.PRO

Compressors	Displacement CC	5	Coolin				00 conder urn Gas 2		+45°C ,		2900 ng T° -10°C	δ
e e	88	Motor			e	vaporatin	ıg T°			evaporatii	ig 1 -10 C	를
Comp	Displa	>	-15	-10	-5	0	5	10	15	Power input(Watt)	COP (W/W)	Weight
AE4425Y	6,69	CSIR	266	342	424	519	633	770	938	199	1,72	9,1
AEZ4425Y	7,6	CSIR	239	320	414	522	641	771	912	205	1,56	9,7
											9%	
			M77	ice	-തത	(am	ลไป้กล	ha (eam			
AE4430Y	8,02	CSIR	294	382	488	613	760	930	1127	237	1,61	9,4
AEZ4430Y	8,8	CSIR	316	404	512	639	784	946	1122	258	1,57	10,2
											3%	
AE4440Y	10,33	CSIR	399	508	637	790	968	1176	1417	302	1,68	9,6
CAE4440Y	12	CSIR	399	519	666	837	1033	1250	1489	342	1,52	10,8
											10%	
AE4450Y	13,24	CSIR	526	672	843	1042	1273	1540	1847	370	1,82	10,5
CAE4448Y	14,2	CSIR	519	654	822	1023	1253	1512	1797	400	1,64	11,9
											10%	
AE4456Y	14.51	CSIR	579	737	921	1133	1380	1664	1990	424	1.74	11
CAE4456Y	16	CSIR	590	744	933	1156	1411	1695	2006	486	1,53	12,5
						- 1100				- 100	12%	12,0
AE4460Y	15,09	CSR	597	766	958	1181	1437	1732	2070	409	1,87	11,3

Private Picture Copyright: WWW.MBSM.PRO

Model NO.	CAE4448Y	Refrigerant Type	Ammonia
Refrigerant	R134A	Voltage	208V/50Hz 230V/60Hz
Horsepower	1/3HP	Capacity(W)	519W
Input Power(Kw)	400W	Oil Charge (Cm3)	450
Net Weight(Kg)	12kg	Cop(W/W)	1.64
Trademark	tecumseh	Transport Package	Wooden Box
Specification	208V/50HZ 230V/60HZ	Origin	France
HS Code	8414309010		

Mbsm_dot_pro_private_PDF_cae4448yTélécharger

Mbsm.Pro , Tecumseh Refrigeration Compressor, CAE9460Z ,R404A refrigerant ,3/8 hp, mhbp, 1/2HP ,1PH(phase) , 220V to 240V

written by Jamila | 11 March 2024 Mbsm.Pro , Tecumseh Refrigeration Compressor ,R404A refrigerant ,1/2HP ,1PH(phase) , 220V to 240V

- Brand Name: Tecumseh
- Certification:RoHS
- Application:Refrigeration Parts
- Type:Refrigeration Compressor



LOW BACK PRESSURE COMPRESSORS

		Nominal	Power (H. P.) 🕫	9	0.	REFRIG	ERATION	CAP/	ACITY A	T 50HZ+			
	COMPRESSOR↔ MODELS↔		Refrige	erant+ ³		Rafed @54.5°C Cond Temp (Watts)⊄								
Туре∳		t.	t	Displac (cm³)		0	Evapo	rating	Tempera	ture₽		3	VOLTAGE.₽	
				t	charge.	-45℃.,	-40℃.,	-35℃.,	-30℃.,	−23. 3 °C.,	-20℃.,	-10℃.,		
+	AEZ2415Z₽	7/16₽	R404A↔	8.143	350₽	43	43	160₽	231₽	355₽	429₽	703₽	220-240V/1/50Hz+	
←	CAE2417Z4 ²	7/16₽	R404A+	11.3↔	350↔	37.8⁴′	62↔	1614	280₽	460↔	557₽	891₽	220-240V/1/50Hz+	
+- +- +- +- +-	CAE2420Z₽	1/2₽	R404A+3	12.6₽	350€	194₽	179₽	232₽	357₽	547€	654₽	1047₽	220-240V/1/50Hz+	
	CAE2424Z₽	5/8₽	R404A+3	15.1€	350₽	228₽	180₽	291₽	442₽	664€	783₽	1199₽	220-240V/1/50Hz+	
	CAJ24284 ^J TAJ2428Z4 ^J	3/4₽	R404A+	15.2€	887+3	ė.	₽	306↔	434₽	628€	773₽	1246₽	220-240V/1/50Hz+ 400V/3/50Hz+	
	CAJ2432Z TAJ2432Z₽	3/4+	R404A+	18.3₽	887+3	331₽	265₽	318₽	510₽	792₽	950₽	1560₽	220-240V/1/50Hz+ 400V/3/50Hz+	
+	CAJ2440Z4 ²	1₽	R404A+	21↔	887₽	532₽	394₽	452₽	647₽	975₽	1166₽	1876₽	220-240V/1/50Hz+	
+ ← PISTON÷	CAJ2446Z4 ¹ TAJ2446Z4 ²	1€	R404A₽	26.15₽	88743	702₽	575₽	549₽	797₽	1194₽	1423₽	2290₽	220-240V/1/50Hz+ 400V/3/50Hz+	
PISTUIN	CAJ2464Z4 ² TAJ2464Z4 ²	1-1/2₽	R404A4	34.454	88743	805€	626₽	723₽	1076₽	1605₽	1902₽	3012₽	220-240V/1/50Hz+ 400V/1/3/50Hz+	
1	FH2480Z4 ² TFH2480Z4 ²	ئ _ب تپ	R404A4	53.2€	1625₽	292₽	420₽	738₽	1319₽	2183₽	266247	4419₽	220-240V/1/50Hz+ 400V/3/50Hz+	
	FH2511Z+/ TFH2511Z+/	347	R404A₽	74.25₽	1625₽	1561₽	1203₽	1380₽	2016₽	3135₽	3796₽	6222₽	220-240V/1/50Hz+ 400V/3/50Hz+	
	TAG2516Z↔ TAGP2516Z↔	447	R404A4	112.5€	1960₽	1696₽	1407€	1743₽	2704₽	4356₽	5335₽	9038₽	400V/3/50Hz₽	
	TAG2522Z TAGP2522Z₽	647	R404A4	134.8€	19604	2541₽	2012₽	2378₽	3542₽	5522₽	66884	11062₽	400V/3/50Hz₽	

PictureS Mbsm Dot Pro : WWW, mbsm, pro

THENEWTWOGENERATIONBRAZILCOMPRESSORS+

-	COMPRESSOR↔ MODELS↔	Nominal	. Power (H. P.) 4		REFRIGERATION CAPACITY AT 50HZ₽								
÷ TYPE ÷			Refrigerant⊄			Rafed 54.5°C Cond Temp (Watts)₽								
		t	÷	Displ aceme			Evapo	rating	Tempera	ature₽			VOLTAGE₽	
		€2		nt (cm³) ₽	-20℃.,	-15℃.,	-10℃.,	-5℃.,	20	+5℃.,	+10℃.,	+15℃.,		
	AE4425Z-FZ1A+	1/5↔	R404A↔	4.24₽	222₽	228₽	290₽	362₽	446₽	545₽	659₽	792₽	220-240V/1/50HZ+	
- 4-	AE4430Z-FZ1A	1/443	R404A4³	5.16₽	216₽	293₽	375₽	466₽	568₽	685₽	821₽	977₽	220-240V/1/50HZ+	
PISTON +	AE4440Z-FZ1A	1/3↔	R404A↔	6.69+3	278₽	377₽	482₽	599₽	730€	881₽	1055€	1257₽	220-240V/1/50HZ+	
+	AE4450Z-FZ1A	7/16₽	R404A↔	8.85₽	369₽	500₽	640₽	795₽	970₽	1170≠	1401₽	1668₽	220-240V/1/50HZ+	
4	AE4460Z-FZ1C+	1/2↩	R404A+	10.33↔	€2	636₽	784₽	959₽	1160₽	1380₽	1630€	1920₽	220-240V/1/50HZ	

4

Tecumseh Compressor₽

		Nominal	. Power (H. P.) +	í.								
	8		Refrigerant+			REFRIGERATION CAPACITY AT 50HZ↔							
+ TYPE	← COMPRESSOR←		t	Displacement (cm³) ↔		Rafed @54.5°C Cond Temp (Watts)₽						VOLTAGE₽	
111E	MODELS↔	ti			Oil charge (cm3) .	Evaporating Temperature+					VOLTHGE+		
		دي		t	ته	-35℃.,	-30℃.,	-25℃.,	-20℃.,	-15℃.,	-10°C.,		
+	RGA/HGA2426Z↔	2/3₽	R404A+ ³	9.50₽	290₽	375₽	474€	590₽	726₽	988₽	1080₽	220-240V/1/50HZ	
ROTARY +	RGA/HGA2432Z←	4/5₽	R404A+3	11.50↔	290€	451₽	567₽	707₽	872₽	1065₽	1290₽	220-240V/1/50HZ	
KOTAKT Y	RGA/HGA2436Z↔	147	R404A+	12.70₽	290₽	508₽	643₽	804₽	994₽	1219₽	1483₽	220-240V/1/50HZ	

PictureS Mbsm Dot Pro : WWW.mbsm.pro

Tecumseh Compressor₽

MEDIUM/HIGH BACK PRESSURE COMPRESSORS4

1		Nomin	al Power	(H.P.)	4	85	PEEPIC	CDATION	V CAD	ACTTV A	T EOUT	. 1		
			Refrige	erant∉ ³			REFRIGERATION CAPACITY AT 50HZ+ Rafed @54.5°C Cond Temp (Watts)+							
+	COMPRESSOR←		t	Displacement (cm³) ≠		8	Marca		VOLTAGE₽					
TYPE +	MODELS₽	t			Oil charge. (cm3	Evaporating Temperature↔							4	
				t		-15℃.₁	-10℃.,	-5℃.,	0.00	+5℃.,	+10℃.,	+15°C.,		
+ +-	RGA/HGA4467Z	1/2₽	R404A+	9.50₽	290₽	679₽	847₽	1047₽	1283₽	1557₽	1872₽	2231₽	220-240V/1/50Hz	
	BGA/HGA4480Z+	2/3₽	R404A₽	11.50₽	290₽	825₽	1017₽	1252₽	1530₽	1851₽	2212₽	2613₽	220-240V/1/50Hz	
+	RGA/HGA4492Z	3/4₽	R404A₽	12.50₽	290₽	905₽	1133₽	1398₽	1706€	2060₽	2468₽	2932₽	220-240V/1/50Hz	
ROTARY	RGA/HGA4512Z	1€	R404A	16.10₽	290₽	1163₽	1438₽	1770₽	2160₽	2609₽	3118₽	3689₽	220-240V/1/50Hz+	
	RGA/HGA4445Y	1/3₽	R134a↔	9.50₽	29047	392₽	493€	618₽	770₽	954₽	1173₽	1430₽	220-240V/1/50Hz+	
	RGA/HGA4450Y	2/5₽	R134a+³	11.50₽	290₽	501€	625¢³	778₽	963₽	1184₽	1445€	1749₽	220-240V/1/50Hz+	
	RGA/HGA4460Y	1/2₽	R134a+³	12.70₽	290₽	537₽	677₽	844₽	1045₽	1287₽	1576₽	1920₽	220-240V/1/50Hz	

PictureS Mbsm Dot Pro : WWW.mbsm.pro



Mbsm.pro, ZEL GTM93AG, 1/3 Hp, Compressor for wine coolers, 200-220V/50Hz 220-230V/60Hz, R134A

written by Jamila | 11 March 2024



Mbsm.pro, ZEL GTM93AG, 1/3 Hp , Compressor for wine coolers ,200-220V/50Hz 220-230V/60Hz, R134A

Place of Origin: China

Product Description

Product Description

ZEL GTM93AG Compressor for wine coolers 200-220V/50Hz 220-230V/60Hz R134A

Specifications

Refrigeration Compressor

Refrigerator, freezer, drinking fountains and home ice cream, Refrigeration Compressor

Application: Refrigerator, freezer, drinking fountains and

home ice cream, ice-making machines and other products

Production Standard: CCC, DVE, RoHS, UL certificate

Packing: Carton

Household Applications

- Freezers
- Refrigerators
- Wine Coolers

Commercial Applications

- Horzontal Freezers
- Merchandisers
- Equipment for professional kitchens
- Dispenser
- Water Coolers
- Wine Coolers
- Ice makers
- Vending Machines

– Minibar

They are the best selling high-tech compressors sold in the world. They are ideal for domestic refrigeration and also for small commercial applications. They are small, have low noise and vibration levels, they achieve the highest levels of efficiency available in the market for this category.

For more details of the refrigeration compressor, please contact us.

Model	Displacement	Height	Motor Type	Cooling capacity	СОР	Power Supply
	cm3	MM		W	W/W	V/Hz
GTM93AG	9.3	183	CSIR	248	1.15	200-220/50
		183	CSIR	290	1.30	220-230/60

Related Keywords

Compressor Wine Coolers , Coolers For Wine Bottles , Air Compressor For Engineerin

China Compressor Wine Coolers , China Coolers For Wine Bottles , China Air Compressor For Engineerin

