Whirlpool, Aspera, NE2125E, LBP, capacitive, start inductive run, hermetic compressor, R22, 1/4Hp++ or 1/3Hp—

Category: compressor written by Lilianne | 18 March 2021 ompressor Aspera NE2125E, LBP - R22, 220-240V / 1 / 50Hz, stroke volume 8.78 cm3, LRA 11.0A, motor type CSIR, capillary tube / expansion valve operation, oil AB 46.Cooling capacity measured for condensation temperature of: 45 ° C, Measurement conditions: ASHRAE Unfortunately the compressor is no longer available. If you would like an offer for an identical alternative, please email us or give us a short call, we will prepare an offer for you.Cooling capacity (W) at To - 10 ° C - 15 ° C - 20 ° C - 25 ° C - 30 ° C

651 517 401 304 226



R22 - LBP Applications					
		DIMENSION			
COMPRESSOR	FREQUENCY	(from -30°C to -5°C evap. temp.)	-		
NE2125E	50 Hz	0.91 mm I.D. × 3.2 m	<u>_</u>		
	60 Hz	0.91 mm I.D. × 2.85 m	-		
NE2134E	50 Hz	0.91 mm I.D. × 2.8 m	157		
	60 Hz	0.91 mm I.D. × 2.5 m	74 <u>12</u>		
T2140E	50 Hz	0.91 mm I.D. × 2.6 m	<u> 19</u>		
	60 Hz	0.91 mm I.D. × 2.3 m	-		
T2155E	50 Hz	1.20 mm I.D. × 3.9 m	-		
	60 Hz	1.20 mm I.D. × 3.5 m	-		
T01(0E	50 Hz	1.20 mm I.D. × 3.3 m	9 <u>11</u>		
T2168E	60 Hz	1.20 mm I.D. × 2.8 m	-		
NJ2178E	50 Hz	1.20 mm I.D. × 3.0 m			

PictureS Mbsm Dot Pro : WWW.mbsm.pro

Private Picture Copyright : WWW.MBSM.PRO

18 19			4			
	asp	era		NE2125	E	
	CE	THERMALLY		220-240V ~ 50H	łz	
	SUCTION	R 22 MADE IN SLOVAKIA	1 PH	WITHOUT STARTING DEVI	CE	
	2611A51		GP	N03MQ395		













Mbsm_dot_pro_private_PDF_ne2125e-Embraco_VerdichterTélécharger

Shipping Class	Default
Scope Of Application	LBP
Delivery Time	2-3 Weeks
Stock Availability	In Stock
Туре	Reciprocating Piston
Condensation Temperature	45 ° C
Manufacturer	Aspera
Manufacturer No.	NE2125E
Power In Hp	1/4 +
Starting Torque	HST
Stroke Volume In Cm3	8.78
Measurement Conditions	Ashrae
Refrigerant	R22
Oil Type	IS046
Series	NE
Condensing Units Compressors	Compressor

 Tension
 220-240V

 Weight In Kg
 10.4