

**Mbsm.pro, Refrigeration,
Compressor, GQR12TG, 3/8+ hp
(big) ++, HBP, 1168W, 1/2 Hp
(LBP) , CSIR, R134A, Starting
Capacitor 80UF, Displacement
12.0cm³**

written by Lilianne | 26 December 2021



Private Picture Copyright : WWW.MBSM.PRO

GQR12TG Freezing



Private Picture Copyright : WWW.MBSM.PRO

The GQR12TG is a hermetic reciprocating compressor manufactured by Sikelan. It is a 3/8 HP compressor that uses R134a refrigerant. It is designed for use in commercial refrigeration applications, such as water dispensers, ice machines, and small freezers.

The GQR12TG has a displacement of 12.8 cc and a cooling capacity of 1168 W. It has a voltage rating of 220-240 V and a frequency rating of 50-60 Hz. The compressor is also equipped with a current relay for starting.

Here are some of the key features of the GQR12TG compressor:

- 3/8 HP
- R134a refrigerant
- 12.8 cc displacement
- 1168 W cooling capacity
- 220-240 V voltage

- 50-60 Hz frequency
- Current relay for starting
- High back pressure design

Vol./Freq.□	220-240V / 50-60Hz
Cooling Capacity□	1168W
C.O.P□	2.20
Horse Power□	3/8+
Refrigerant□	R134A
Application□	HBP
The Evaporating Temperature (W)□	7.2°C

- 1)GQR12TG, WZ series, use R134A refrigerant;
- 2)Voltage application 220V to 240V;
- 3)Frequency for 50/60HZ;
- 4)Motor type: CSIR;
- 5)Cooling type: Fan;
- 6)Starting device is Current Starting Relay;
- 7)Application: Middle/Hight Back Pressure;
- 8)Nominal power is 3/8+HP;
- 9)COP is 2.3 with the cooling capacity 1168W.

1. Product Performance

- 1)GQR12TG, WZ series, use R134A refrigerant;
- 2)Voltage application 220V to 240V;
- 3)Frequency for 50/60HZ;
- 4)Motor type: CSIR;
- 5)Cooling type: Fan;
- 6)Starting device is Current Starting Relay;
- 7)Application: Middle/Hight Back Pressure;
- 8)Nominal power is 3/8+HP;
- 9)COP is 2.2 with the cooling capacity 1168W.

Basing on Test Condition(ASHRAE)

Evaporating Temperature: -23.3 degree
 Ambient Temperature: 35 degree
 Subcooling Temperature: 46.1 degree
 Condensing Temperature: 54.4 degree
 Suction Temperature: 35 degree

2.Compressor Specification

Serial	Model	HP	(V/Hz)	Displacement (cm3)	Cooling Capacity -ASHRAE	Motor type	Starting Device	Starting capacitor (uF)	Running capacitor (uF)	Cooling																		
Test Conditions:+7.2°C(45F)					10°C(50F)																							
W	Btu/h	W	Btu/h	W	Btu/h	W	Btu/h	Capacity (W)	Capacity (Btu/h)	Input Power(w)	Current (A)	COP (W/W)	COP (Btu/Wh)	W	Btu/h										PTC/Current Starting Relay	/	/	F
L	GQR30TG	1/10	220V/50Hz	3.0	115	392	145	495	185	631	230	785	310	1058	140	0.9	2.2	7.56	365	1245	RSIR	/	/	F				
GQR35TG	1/9	220V/50Hz	3.5	135	461	175	597	195	665	285	972	430	1467	195	1.1	2.2	7.52	475	1621	RSIR	/	/	F					
MS	GQR45TG	1/6	220V/50Hz	4.5	176	601	230	785	280	955	350	1194	480	1638	220	1.2	2.2	7.44	525	1791	RSIR	/	/	F				
GQR55TG	1/6+	220V/50Hz	5.5	188	641	245	836	310	1058	390	1331	525	1791	250	1.3	2.1	7.17	575	1962	RSIR	/	/	F					
MK	GQR60TG	1/4	220V/50Hz	6.5	258	880	335	1143	435	1484	545	1860	665	2269	290	1.7	2.3	7.82	705	2405	RSIR	/	/	F				
GQR70TG	1/4	220V/50Hz	7.0	285	972	370	1262	480	1638	595	2030	720	2457	340	1.9	2.1	7.23	765	2610	RSIR	/	/	F					
GQR80TG	1/4+	220V/50Hz	8.0	324	1105	420	1433	550	1877	680	2320	810	2764	370	2.0	2.2	7.47	855	2917	RSIR	/	/	F					
GQR90TG	1/3-	220V/50Hz	9.1	365	1245	474	1617	621	2119	768	2620	910	3105	420	2.2	2.2	7.39	955	3258	RSIR	/	/	F					
WZ	GQR80TG	1/4+	220V/50Hz	8.0	324	1105	420	1433	550	1877	680	2320	810	2764	370	2.0	2.2	7.47	855	2917	CSIR	80	/	F				
GQR90TG	1/3-	220V/50Hz	9.1	365	1245	474	1617	621	2119	768	2620	910	3105	420	2.2	2.2	7.39	955	3258	CSIR	80	/	F					
GQR11TG	3/8	220V/50Hz	11.0	412	1406	536	1829	702	2395	868	2962	1034	3528	450	2.7	2.3	7.84	1079	3682	CSIR	80	/	F					
GQR12TG	3/8+	220V/50Hz	12.8	467	1593	606	2068	793	2706	981	3347	1168	3985	530	3.2	2.2	7.52	1208	4122	CSIR	80	/	F					
GQR14TG	1/2	220V/50Hz	14.2	527	1798	685	2337	896	3057	1108	3780	1320	4504	580	3.4	2.3	7.77	1365	4657	CSIR	80	/	F					
GQR16TG	1/2+	220V/50Hz	15.3	580	1979	754	2573	1012	3453	1252	4272	1492	5091	640	3.8	2.3	7.95	1535	5237	CSIR	80	/	F					
GQR19TG	3/4	220V/50Hz	19.0	755	2576	940	3207	1175	4009	1255	4282	1850	6312	804	4.5	2.3	7.85	1895	6466	CSIR	80	/	F					

KONOR	Displ.	power	Motor type	V/Hz	Cooling capacity W	Net Weight KG
GQR60AA	6	1/6	RSIR	220-240V/50Hz	140	9.4
GQR70AA	6.6	1/5	RSIR	220-240V/50Hz	165	9.4
GQR80AA	8.1	1/4	RSIR	220-240V/50Hz	198	9.4
GQR90AA	9.1	1/4	RSIR	220-240V/50Hz	220	10.1
GQY99AA	9.9	1/4	RSIR	220-240V/50Hz	270	10.9
GQY12AF	11.8	1/3	CSIR	220-240V/50Hz	325	10.56
GQY16AF	16.2	3/8	CSIR	220-240V/50Hz	380	12.1
GP16MG	16.2	5/8	CSIR	220-240V/50Hz	870	12.5
GP12MG	11.8	5/8	CSIR	220-240V/50Hz	656	10.9
GP12TG	11.8	3/8	CSIR	220-240V/50Hz	1140	11.8
GQR80TG	8.1	1/4	CSIR	220-240V/50Hz	730	9.8
GQR90TG	9.1	1/4	CSIR	220-240V/50Hz	830	10.5
GQR60TG	6	1/5	CSIR	220-240V/50Hz	520	9.8



Private Picture Copyright : WWW.MBSM.PRO

153	L QD35HG	1/11	3,5			75	штг	16720
154	ML ADW51	1/6	5,1			125	штг	19360
155	ML ADW57	1/5-	5,7			135	штг	19800
156	ML ADW66	1/4-	6,6			165	штг	0
157	MX ADW77	1/4	7,7			185	штг	0
158	MX ADW86	1/4+	8,6			200	штг	23760
159	MX ADW91	1/3-	9,1			220	штг	0
160	MQ ADW110	1/3	11,0			270	штг	0
161	MQ ADW128	3/8+	12,8			320	штг	27720
162	MQ ADW142	1/2-	14,2			350	штг	28600
163	MQ ADW153	1/2	15,3			380	штг	29040
164	MQ ADW168	1/2+	16,8			430	штг	29480
№	Модель HBP R134a	HP	см3/час	Мотор	Обмотка	Мощность, ватт 7,2/54,4C	Ед. изм.	Цена, тг.
165	MQ GQR12TG	3/8+	12,7	SIR	медь (Cu)	1300	штг	29480
166	MQ GQR14TG	1/2	14,3			1450	штг	30800
167	MQ GQR16TG	1/2+	15,3			1490	штг	32120
№	Модель LBP R404a	HP	см3/час	Мотор	Обмотка	Мощность, ватт -23,3/54,4C	Ед. изм.	Цена, тг.
168	MQ GQR80K	1/3+	8,0	CSIR	медь (Cu)	465	штг	30800
169	MQ GQR90K	1/2-	9,0			515	штг	31680
170	MD GQR11K	1/2	11,0			565	штг	0
171	MD GQR12K	3/4	12,1			640	штг	45320
172	MD GQR14K	3/4	14,3	CSR	медь (Cu)	750	штг	47080
173	MD GQR16K	4/5	16,2			850	штг	47960
174	MD GQR19K	7/8	19,0			920	штг	49280

Private Picture Copyright : WWW.MBSM.PRO



Private Picture Copyright: WWW.MBSM.PRO

Mbsm_dot_pro_private_PDF_Gqr12tgTélécharger

