

COMPRESSOR DEFINITION

Designation	NE K1116Z
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	268EA47

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSIR-RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 254 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 254 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	16.2	[kgf/cm ²] (230 psig)	/ °C - °F
9.2 Peak (gauge)	20.6	[kgf/cm ²] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	7.37	[cm ³] (0.450 cu.in)
2.1 Bore [mm]	24.282	
2.2 Stroke [mm]	15.920	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	10.8	[kg] (23.81 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	V230	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	4(400)	[µF(VAC minimum)]
5 Motor protection	T0503/07	
6 Start winding resistance	17.60	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	13.20	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	5.30	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.82	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	IMQ	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
663	167	194	135	0.60	3.77	4.92	1.24	1.44

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static				(Condensing temperature 35°C (+95°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	382	96	112	85	0.41	2.16	4.51	1.14	1.32
-30	(-22)	524	132	154	99	0.48	2.97	5.32	1.34	1.56
-25	(-13)	698	176	204	114	0.54	3.96	6.11	1.54	1.79
-20	(- 4)	910	229	267	131	0.61	5.18	6.93	1.75	2.03
-15	(+ 5)	1168	294	342	149	0.68	6.67	7.84	1.97	2.30
-10	(+14)	1480	373	434	167	0.76	8.48	8.87	2.24	2.60

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static				(Condensing temperature 45°C (+113°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	339	85	99	86	0.40	1.92	3.96	1.00	1.16
-30	(-22)	482	122	141	102	0.48	2.73	4.70	1.18	1.38
-25	(-13)	653	165	191	121	0.56	3.71	5.39	1.36	1.58
-20	(- 4)	859	216	252	141	0.64	4.89	6.07	1.53	1.78
-15	(+ 5)	1107	279	324	162	0.73	6.32	6.81	1.72	2.00
-10	(+14)	1404	354	411	184	0.83	8.04	7.64	1.93	2.24

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static				(Condensing temperature 55°C (+131°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	281	71	82	83	0.39	1.59	3.40	0.86	0.99
-30	(-22)	426	107	125	104	0.48	2.41	4.09	1.03	1.20
-25	(-13)	594	150	174	126	0.58	3.37	4.70	1.18	1.38
-20	(- 4)	793	200	232	151	0.68	4.51	5.27	1.33	1.54
-15	(+ 5)	1030	260	302	176	0.79	5.88	5.86	1.48	1.72
-10	(+14)	1312	331	385	202	0.91	7.52	6.50	1.64	1.91

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted parallel to Base Plate		
3.3 PROCESS	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		