

R600a COMPRESSOR R600a 压缩机

Application 应用类型	Model 压缩机型号	Displ. 气缸容积 Cm³	Power 马力	Capacity 制冷量		Inp.Power 功率	Performance 效率		Motor Type	Capacitor 电容		Cooling Type
			Нр	W	Btu/h	W	COP W/W	EER Btu/Wh	电机型式	Running µ F	Starting µ F	冷却方式
LBP	220-240V/50Hz											
	PW3.0B	4.99	1/12	70	239	58	1.21	4.12	RSIR			S
	PW4.0B	5.68	1/8	90	307	72	1.25	4.26	RSIR			s
	PW58BM	6.09	1/8+	100	341	82	1.22	4.16	RSIR			s
	PW5.0B	7.07	1/6-	115	392	92	1.25	4.26	RSIR			S
	PW7.0B	8.05	1/6+	135	461	108	1.25	4.27	RSIR			S
	PW9.0B	9.03	1/5	150	512	115	1.30	4.44	RSIR			S
	PW10.0B	10.10	1/4-	170	580	131	1.30	4.44	RSIR			S
	PW12.0B	11.33	1/4+	190	648	146	1.30	4.43	RSIR			s
	DFB30LF	3.51	1/15	55	188	48	1.05	3.92	RSIR	/		S
	DFB30L-1F	3.66	1/14-	55	188	39	1.30	4.82	RSCR	3.5		S
	DFB35L	4.29	1/10-	65	222	50	1.30	4.44	RSCR	3.5		S
	DFB60L DFB69L	5.68 6.17	1/9	90	307	64	1.40	4.78	RSCR RSCR	/		S
			1/9	90	307	60	1.50	5.12		3.5		s
			1/8+	100	341	69	1.45	4.94		/		s
			1/8+	100	341	62.5	1.60	5.46		3.5		S
			1/6-	115	392	82	1.41	4.81		/		S
			1/6-	115	392	76	1.51	5.15	RSCR	3.5		S
	DFB79L	8.05	1/6+	135	461	96	1.40	4.78		/		S
			1/6+	135	461	90	1.50	5.12		3.5		S
	DFB90L	9.03	1/5	150	512	103	1.45	4.95	RSCR	/		S
			1/5	150	512	96	1.56	5.32		3.5		S
	DFB60S	6.17	1/8+	100	341	61	1.63	5.56	RSCR	3.5		S
LBP	DFB69S	7.07	1/6-	115	392	70	1.65	5.62	RSCR	3.5		S
	DFB79S	8.05	1/6+	135	461	81	1.67	5.70	RSCR	3.5		S
	DFB90S	9.03	1/5	150	512	91	1.65	5.63	RSCR	3.5		S
	DFB35T	4.29	1/10-	65	222	42	1.55	5.29	RSCR	3.5		s
	DFB45T	4.99	1/9	80	273	52.5	1.62	5.20	RSCR	3.5		s
	DFB60T	6.17	1/8+	100	341	60	1.66	5.68	RSCR	3.5		s
	DFB69T	7.07	1/6-	115	392	67	1.72	5.85	RSCR	3.5		S
	DFB79T	8.05	1/6+	135	461	78	1.73	5.91	RSCR	3.5		S
	DFB90T	8.92	1/5	150	512	85	1.75	6.02	RSCR	3.5		s
	DFB103T	10.71	1/4-	170	580	98	1.73	5.92	RSCR	3.5		s
	DFB115T	11.95	1/4	190	648	114	1.67	5.68	RSCR	3.5		S
	220–240V/50.60Hz											
	PW48BMF	4.29	1/10+	70	239	61	1.15	3.92	RSIR	/		S
	DFB55KF	5.68	1/8+	100	341	76	1.31	4.47	RSIR	1		S
	DFB69LKF	7.07	1/6+	130	444	87	1.50	5.12	RSCR	3.5		S
	DFB79LKF	8.05	1/5	143	488	95	1.50	5.12	RSCR	3.5		S
	110–120		1,0	1 10	100		1.00	0.12	1,0011	0.0		0
	DFB30DF	3.15	1/14	55	188	44	1.25	4.27	RSIR	/		S
	DFB30DLF	3.15	1/14	55	188	42	1.30	4.48	RSCR	8		S
	DFB40DF	4.29	1/12-	74	252	61	1.21	4.12	RSIR	8		S
	DFB40DLF	4.29	1/12-	75	256	56	1.35	4.61	RSCR	8		S
	DFB50DF	4.99	1/9	87	297	67	1.30	4.44	RSIR	/		S
	DFB50DLF	4.99	1/9	87	297	60	1.46	4.98	RSCR	8		S
	DFB55DF	5.68	1/8+	100	341	74	1.35	4.60	RSIR	/		S
	DFB55DLF	5.68	1/8+	100	341	65	1.53	5.22	RSCR	8		S
	DFB60DF	6.37	1/6-	120	409	86	1.40	4.77	RSIR	/		S
	DFB60DLF	6.37	1/6-	120	409	78	1.53	5.21	RSCR	8		S
	DFB70DF	7.07	1/6+	138	471	97	1.42	4.85	RSIR	/		S
	DFB70DLF	7.07	1/6+	138	471	89	1.55	5.29	RSCR	8		S