

Mbsm.pro, White Whale, THailand, 365 L, WRF-404HT, TWH White, SLS Slver, PWH While, 1.4 A, 187 W, r134 a, 105 g, Compressor, Hitachi, FL1257-sr, 1/5 hp

Category: Refrigerator

written by Lilianne | 1 October 2023



Private Picture Copyright : WWW.MBSM.PRO

Mbsm.pro, White Whale, THailand, 365 L WRF-404HT, TWH White, SLS Slver, PWH While, 1.4 A, 187 W, r134 a, 105 g, Compressor, Hitachi, FL1257-sr, 1/5 hp

200 / 220 / 50/60 HZ												MODEL	
كمية الزيت cm3	الغريون	التطبيق	COOLING CAPACITY					الإزاحة Displ.CC	الأمبير RLA	Freq HZ	القدرة المسحوبة		
			W 7.2+	W -5	W -23	BTU	k CAL/HR				W		H P
240	R600	LBP			147	500	126	9.0		50	110	1/7	CL1188
					176	599	151			60			
370	R600	LBP			145	496	125	9.7		50	120	1/6	CL1297
					169	575	145			60			

200 / 220 / 50/60 HZ												MODEL	
مكلف التشغيل	الغريون	التطبيق	COOLING CAPACITY					الإزاحة Displ.CC	الأمبير RLA	Freq HZ	القدرة المسحوبة		
			W 7.2+	W -5	W -23	BTU	k CAL/HR				W		H P
4	R600a	LBP			115	392	99	6.8		50			CL0768-SC
4	R600a	LBP			125	426	107	7.5		50			CL0875-SD
4	R600a	LBP			125	426	107	7.5		50			CL0875-SE
4	R600a	LBP			145	495	125	8.8		50			CL1188-SE
4	R600a	LBP			145	495	125	8.8		50			CL1188-SF
4	R600a	LBP			145	495	125	8.8		50			CL1188-SG
4	R600a	LBP			145	495	125	8.8		50			CL1188-SH
4	R600a	LBP			165	563	142	10.3		50			CL1310-SJ
4	R600a	LBP			165	563	142	10.3		50			CL1310-SK
4	R600a	LBP			165	563	142	10.3		50			CL1310-SL
4	R600a	LBP			165	563	142	10.3		50			CL1310-SM
4	R600a	LBP			180	614	155	10.9		50			CL1411-SA
4	R600a	LBP			180	614	155	10.9		50			CL1411-SB
4	R600a	LBP			180	614	155	10.9		50			CL1411-SC
4	R600a	LBP			180	614	155	10.9		50			CL1411-SD
4	R600a	LBP			220	751	189	13.6		50			CL1613-SA
4	R600a	LBP			220	751	189	13.6		50			CL1613-SB
4	R600a	LBP			220	751	189	13.6		50			CL1613-SC
4	R600a	LBP			220	751	189	13.6		50			CL1613-SD
4	R600a	LBP			230	785	198	14.3		50			CL1714-SA
4	R600a	LBP			230	785	198	14.3		50			CL1714-SB
4	R600a	LBP			230	785	198	14.3		50			CL1714-SC
4	R600a	LBP			230	785	198	14.3		50			CL1714-SD

Private Picture Copyright : WWW.MBSM.PRO

200 / 220 / 50/60 HZ												MODEL	
كمية الزيت cm3	الغريون	التطبيق	COOLING CAPACITY					الإزاحة Displ.CC	الأمبير RLA	Freq HZ	القدرة المسحوبة		
			W 7.2+	W -5	W -23	BTU	k CAL/HR				W		H P
280	R404a	LBP			340	1159	292	6.2		50	300	1/2	RL3062
					399	1361	343			60			
280	R404a	LBP			380	1298	327	6.8		50	350	1/2	RL3568
					450	1536	387			60			
280	R404a	LBP			420	1432	361	7.5		50	400	1/2	RL4075
					480	1639	413			60			
280	R404a	LBP			500	1706	430	8.8		50	450	1/2	RL4588
					580	1980	499			60			

200 / 220 / 50/60 HZ												MODEL	
كمية الزيت cm3	الغريون	التطبيق	COOLING CAPACITY					الإزاحة Displ.CC	الأمبير RLA	Freq HZ	القدرة المسحوبة		
			W 7.2+	W -5	W -23	BTU	k CAL/HR				W		H P
240	R600	LBP			147	500	126	9.0		50	110	1/7	CL1188
					176	599	151			60			
370	R600	LBP			145	496	125	9.7		50	120	1/6	CL1297
					169	575	145			60			

Private Picture Copyright : WWW.MBSM.PRO

مكثف التبريد	مكثف التشغيل	الفريون	التطبيق	200 / 220 / 50/60 HZ COOLING CAPACITY				الإزاحة Displ.CC	الأمبير RLA	Freq HZ	القدرة المسحوبة		MODEL	
				W 7.2+	W -5	W -23	B T U				k CAL/HR	W		H P
						R134a	HBP				328			
		R134a	HBP	375			1279	322	3.9	50			FH0739-SE	
		R134a	HBP	440			1501	378	4.5	50			FH1045-SC	
		R134a	HBP	460			1569	396	4.7	50			FH1247-SA	
		R134a	HBP	517			1764	445	5.2	50			FH1552-SE	
		R134a	HBP	570			1945	490	5.7	50			FH1657-SA	
60	10	R134a	HBP	620			2115	533	6.2	50			FH1762-SA	
60	10	R134a	HBP	685			2337	589	6.8	50			FH1868-SA	
60	10	R134a	HBP	770			2627	662	7.5	50			FH2075-SH	
60	10	R134a	HBP	890			3037	765	8.8	50			FH2588-SM	
60	10	R134a	HBP	980			3344	843	9.7	50			FH2697-SA	
60	10	R134a	HBP	1040			3548	894	10.3	50			FH2710-SA	
60	20	R134a	HBP	1140			3890	980	10.9	50			FH2711-SD	
60	20	R134a	HBP	1450			4947	1247	14.3	50			FH3014-SG	

كمية الزيت cm3	الفريون	التطبيق	200 / 220 / 50/60 HZ COOLING CAPACITY				الإزاحة Displ.CC	الأمبير RLA	Freq HZ	القدرة المسحوبة		MODEL	
			W 7.2+	W -5	W -23	B T U				k CAL/HR	W		H P
			200	R134a	HBP	320							1091
			361			1230	310		60				
270	R134a	HBP	376			1282	323	3.9	50	75	1/10	FH0739	
			430			1468	370		60				
270	R134a	HBP	450			1536	387	4.5	50	100	1/6	FH1045	
			520			1774	447		60				
270	R134a	HBP	520			1774	447	5.2	50	150	1/5	FH1552	
			600			2047	516		60				
350	R134a	HBP	761			2595	654	7.0	50	200	1/4	FH2075	
			880			3004	757		60				
350	R134a	HBP	890			3036	765	9.0	50	250	1/3	FH2588	
			1000			3412	860		60				

Private Picture Copyright : WWW.MBSM.PRO

ملاحظات	مكثف التشغيل	الفريون	التطبيق	200 / 220 / 50/60 HZ COOLING CAPACITY				الإزاحة Displ.CC	الأمبير RLA	Freq HZ	القدرة المسحوبة		MODEL	
				W 7.2+	W -5	W -23	B T U				k CAL/HR	W		H P
					4	R134a	LBP							130
	4	R134a	LBP			143	488	123	5.2	50			FL11S52NAJ	
	4	R134a	LBP			160	546	138	5.7	50			FL12S57NAQ	
	4	R134a	LBP			160	546	138	5.7	50			FL12S57NAP	
	4	R134a	LBP			165	563	142	6.2	50			FL14S62NAE	
	4	R134a	LBP			165	563	142	6.2	50			FL14S62NAF	
	4	R134a	LBP			185	631	159	6.8	50			FL15S68NAQ	
	4	R134a	LBP			185	631	159	6.8	50			FL15S68NAP	
	4	R134a	LBP			185	631	159	6.8	50			FL15S68NAR	
	4	R134a	LBP			185	631	159	6.8	50			FL15S68NAS	
	4	R134a	LBP			200	682	172	7.5	50			FL18S75NAL	
	4	R134a	LBP			200	682	172	7.5	50			FL18S75NAH	
	4	R134a	LBP			200	682	172	7.5	50			FL18S75NAJ	
	4	R134a	LBP			200	682	172	7.5	50			FL18S75NAM	
	4	R134a	LBP			260	887	224	8.8	50			FL20S88NAV	
	4	R134a	LBP			260	887	224	8.8	50			FL20S88NAW	
	4	R134a	LBP			260	887	224	8.8	50			FL20S88NAX	
	4	R134a	LBP			260	887	224	8.8	50			FL20S88NAY	

Private Picture Copyright : WWW.MBSM.PRO

200 / 220 / 50/60 HZ														
ملاحظات	كمية الزيت cm3	الفرغون	التطبيق	COOLING CAPACITY					الإزاحة Displ.CC	الأمبير RLA	Freq HZ	القدرة المسحوبة		MODEL
				W 7.2+	W -5	W -23	BTU	k CAL/HR				W	H P	
	300	R134a	LBP			200	682	172	7.5		50	7.5		FL1875-T
	300	R134a	LBP			232	792	199			60			
	300	R134a	LBP			263	897	226	8.8		50	8.8		FL2088-T
						290	989	249			60			
	300	R134a	LBP			181	618	156	6.8		50	6.8		FL1568-R
RSCR	240	R134a	LBP			95	324	82	3.4		50	3.4		FL0634-S
RSIR	270	R134a	LBP			82	280	71	3.4		50	3.4		FL0634-S
200 / 220 / 50/60 HZ														
ملاحظات	كمية الزيت cm3	الفرغون	التطبيق	COOLING CAPACITY					الإزاحة Displ.CC	الأمبير RLA	Freq HZ	القدرة المسحوبة		MODEL
				W 7.2+	W -5	W -23	BTU	k CAL/HR				W	H P	
RSIR	270	R134a	LBP			94			3.9					FL0739-S*
RSIR	270	R134a	LBP			117			4.5					FL0845-S*
RSIR	270	R134a	LBP			121			5.2					FL10525*
RSCR	260	R134a	LBP			136			5.2					FL1152-S*
RSIR	280	R134a	LBP			134			5.2					FL1152-S*
RSIR	240	R134a	LBP			136			5.7					FL1157-S*
RSIR	240	R134a	LBP			150			5.7					FL1257-S*
RSCR	240	R134a	LBP			173			5.7					FL1257-S*
RSIR	310	R134a	LBP			145			6.2					FL1262-S*
RSIR	310	R134a	LBP			165			6.2					FL1462-S*
RSCR	310	R134a	LBP			185			6.2					FL1462-S*
CSIR	310	R134a	LBP			180			6.8					FL1568-S*
RSIR	310	R134a	LBP			200			6.8					FL1568-S*
RSCR	310	R134a	LBP			200			6.8					FL1568-S*
RSIR	335	R134a	LBP			215			7.5					FL1875-S*
RSIR	310	R134a	LBP			208			7.5					FL1875-S*
RSIR	300	R134a	LBP			207			8.8					FL1888-S*
CSR	380	R134a	LBP			256			8.8					FL2088-S*
RSCR	300	R134a	LBP			245			8.8					FL2088-S*

# White Whale

WRF-4040HT TWH White  
WRF-4040HT SLS Silver  
WRF-4040HT PWH White



Star rate

RATED VOLTAGE	220-240 V	50 Hz
RATED CURRENT	1.4	A
RATED INPUT	187	W
CLIMATE CLASS	ST	
DEFROSTING INPUT	160	W
REFRIGERANT R134a	0.105	kg
NET CAPACITY	365	Litres
WEIGHT	65	kg

Made in Thailand

SERIAL NO. **2120801297**

HCPT (Thailand)Ltd.

200 / 220 / 50/60 HZ													
كمية الزيت cm3	الفرغون	التطبيق	COOLING CAPACITY					الإزاحة Displ.CC	الأمبير RLA	Freq HZ	القدرة المسحوبة		MODEL
			W 7.2+	W -5	W -23	BTU	kCAL/HR				W	H P	
200	R134a	LBP			78	266	67	3.0		50	65	1/12	FL0634
					90	306	77			60			
270	R134a	LBP			95	325	82	3.9		50	75	1/10	FL0739
					108	369	93			60			
270	R134a	LBP			105	357	90	4.5		50	85	1/8	FL0845
					117	401	101			60			
270	R134a	LBP			120	409	103	5.2		50	100	1/6	FL1052
					140	476	120			60			
240	R134a	LBP			135	460	116	5.7		50	110	1/6	FL1157
					158	540	136			60			
320	R134a	LBP			150	512	129	6.2		50	125	1/5	FL1262
					170	579	146			60			
300	R134a	LBP			185	631	159	7.5		50	160	1/5	FL1675
					211	718	181			60			
300	R134a	LBP			215	734	185	8.8		50	180	1/4	FL1888
					250	853	215			60			

200 / 220 / 50/60 HZ													
كمية الزيت cm3	الفرغون	التطبيق	COOLING CAPACITY					الإزاحة Displ.CC	الأمبير RLA	Freq HZ	القدرة المسحوبة		MODEL
			W 7.2+	W -5	W -23	BTU	kCAL/HR				W	H P	
270	R134a	LBP			131	448	113	5.0		50	110	1/6	FL1152
					155	528	133			60			
240	R134a	LBP			150	512	129	5.7		50	125	1/5	FL1257
					176	599	151			60			
320	R134a	LBP			160	548	138	6.2		50	140	1/5	FL1462
					180	615	155			60			
300	R134a	LBP			185	631	159	6.8		50	150	1/5	FL1568
					209	714	180			60			
300	R134a	LBP			185	631	159	7.5		50	180	1/4	FL1875
					245	837	211			60			
300	R134a	LBP			250	853	215	8.8		50	200	1/3	FL2088
					295	1008	254			60			

Private Picture Copyright : WWW.MBSM.PRO

Code No.	Model	HP	Capacity (W)	Current (A)	Efficiency COP (w/w)	Voltage / Frequency
<b>R134a Models</b>						
R012001	FL 06S34-TAB	1/12	85	0.70	0.93	220V – 240V / 50Hz
R012002	FL 0739-SQ	1/10	114	0.72	1.20	
R012003	FL 0847-SD	1/8	130	0.83	1.19	
R012005	FL 1152-SB	1/6	143	0.82	1.27	
R012006	FL 1257-SR	1/5	160	0.90	1.25	
R012007	FL 14S62-TAD	1/5	175	0.95	1.30	
R012008	FL 1568-SQ	1/4	200	1.11	1.30	
R012009	FL 20S88-TAC	1/3	255	1.50	1.25	
R012010	FL1888-SE	1/3	245	1.51	1.25	
<b>R600a Models</b>						
	CL 0545-SZ	1/12	62	0.70	1.12	220V – 240V / 50Hz
	CL 1297-SA	1/5	156	0.90	1.46	
	CL 1310-SA	1/5+	163	0.95	1.48	
<b>R600a Models (Inverter)</b>						
	CL 1588-DZ	1/6	134	0.83	1.62	220V – 240V / 50Hz
	CL 1610-DL	1/5	160	0.90	1.65	

Private Picture Copyright : WWW.MBSM.PRO



Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)